

RB系列薄壁交叉滚子轴承

产品名称	RB系列薄壁交叉滚子轴承
公司名称	洛阳广实机械有限公司
价格	1.00/套
规格参数	是否标准件:标准件 样品或现货:样品 品牌:GS
公司地址	洛阳市伊川县水寨镇姬磨村
联系电话	86 0379 68449379 13592062007

产品详情

是否标准件
品牌
类型

标准件
GS
其他

样品或现货
滚动体类型

样品
圆柱滚子

轴径	型号	主要尺寸							基本的额定负荷(径向)	
		内径d	外径d	滚子节圆直径dp	宽度b b1	油孔			ckn	c0kn
						a	b	r		
20	rb 2008	20	36	27	8	2	0.8	0.8	3.23	3.10
25	rb 2508	25	41	32	8	2	0.8	0.8	3.63	3.83
30	rb 3010	30	55	41.5	10	2.5	1	1	7.35	8.36
35	rb 3510	35	60	46.5	10	2.5	1	1	7.64	9.12
40	rb 4010	40	65	51.5	10	2.5	1	1	8.33	10.6
45	rb 4510	45	70	56.5	10	2.5	1	1	8.62	11.3
50	rb 5013	50	80	64	13	2.5	1.6	1	16.7	20.9
60	rb 6013	60	90	74	13	2.5	1.6	1	18.0	24.3
70	rb 7013	70	100	84	13	2.5	1.6	1	19.4	27.7
80	rb 8016	80	120	98	16	3	1.6	1	30.1	42.1
90	rb 9016	90	130	108	16	3	1.6	1.5	31.4	45.3
100	rb 10016	100	140	119.3	16	3.5	1.6	1.5	31.7	48.6
	rb 10020		150	123	20	3.5	1.6	1.5	33.1	50.9
110	rb 11012	110	135	121.8	12	2.5	1	1	12.5	24.1
	rb 11015		145	126.5	15	3.5	1.6	1	23.7	41.5
	rb 11020		160	133	20	3.5	1.6	1.5	34.0	54.0
120	rb 12016	120	150	134.2	16	3.5	1.6	1	24.2	43.2
	rb 12025		180	148.7	25	3.5	2	2	66.9	100
130	rb 13015	130	160	144.5	15	3.5	1.6	1	25.0	46.7

	rb 13025		190	158	25	3.5	2	2	69.5	107	
140	rb 14016	140	175	154.8	16	2.5	1.6	1.5	25.9	50.1	
	rb 14025			200	168	25	3.5	2	2	74.8	121
150	rb 15013	150	180	164	13	2.5	1.6	1	27.0	53.5	
	rb 15025			210	178	25	3.5	2	2	76.8	128
	rb 15030			230	188	30	4.5	3	2	100	156
160	rb 16025	160	220	188.6	25	3.5	2	2	81.7	135	
170	rb 17020	170	220	191	20	3.5	1.6	2	29.0	62.1	
180	rb 18025	180	240	210	25	3.5	2	2	84.0	143	
190	rb 19025	190	240	211.9	25	3.5	1.6	1.5	41.7	82.9	
200	rb 20025	200	260	230	25	3.5	2	2.5	84.2	157	
	rb 20030			280	240	30	4.5	3	2.5	114	200
	rb 20035			295	247.7	35	5	3	2.5	151	252
220	rb 22025	220	280	250.1	25	3.5	2	2.5	62.3	171	
240	rb 24025	240	300	269	25	3.5	2	3	68.3	145	
250	rb 25035	250	310	277.5	25	3.5	2	3	69.3	150	
	rb 25030			330	287.5	30	4.5	3	3	126	244
	rb 25040			355	300.7	40	6	3.5	3	195	348
300	rb 30025	300	360	328	25	3.5	2	3	76.3	178	
	rb 30035			395	345	35	5	3	3	183	367
	rb 30040			405	351.6	40	6	3.5	3	212	409
350	rb 35020	350	400	373.4	20	3.5	1.6	3	54.1	143	
400	rb 40035	400	480	440.3	35	5	3	3.5	156	370	
	rb 40040			510	453.4	40	6	3.5	3.5	241	531
450	rb 45025	450	500	474	25	3.5	1.6	1.5	61.7	182	
500	rb 50025	500	550	524.2	25	3.5	1.6	1.5	65.5	201	
	rb 50040			600	548.8	40	6	3	3.5	239	607
	rb 50050			625	561.6	50	6	3.5	3.5	267	653
600	rb 60040	600	700	650	40	6	3	4	264	721	
700	rb 70045	700	815	753.5	45	6	3	4	281	836	
800	rb 80070	800	950	868.0	70	6	4	5	468	1330	
900	rb 90070	900	1050	969	70	6	4	5	494	1490	
1000	rb 1000110	1000	1250	1114	110	6	6	6	1220	3220	
1250	rb 1250110	1250	1500	1365.8	110	6	4	6	1350	3970	