

青岛NORYL EM7100

产品名称	青岛NORYL EM7100
公司名称	东莞市辉众塑胶有限公司
价格	.00/个
规格参数	
公司地址	东莞市樟木头镇塑胶原料市场壹期新一栋4号（注册地址）
联系电话	86-0769-82863609 13268638988

产品详情

代理

1PPE+PSSABIC Noryl 534 2PPE+PSSABIC Noryl 731 3PPE+PSSABIC Noryl 731H4PPE+PSSABIC Noryl BN30 5PPE+PSSABIC Noryl BN31 6PPE+PSSABIC Noryl BN9003G7PPE+PSSABIC Noryl CRX2201 8PPE+PSSABIC Noryl EM6100 9PPE+PSSABIC Noryl EM6100F 10PPE+PSSABIC Noryl EM6101 11PPE+PSSABIC Noryl EM7100 12PPE+PSSABIC Noryl EM7301F 13PPE+PSSABIC Noryl EM7304F 14PPE+PSSABIC Noryl EM7430 15PPE+PSSABIC Noryl EN18516PPE+PSSABIC Noryl EN212 17PPE+PSSABIC Noryl EN265 18PPE+PSSABIC Noryl ENG265 19PPE+PSSABIC Noryl EXNL0143 20PPE+PSSABIC Noryl EXNL0353 21PPE+PSSABIC Noryl EXNL0357 22PPE+PSSABIC Noryl EXNL1117 23PPE+PSSABIC Noryl EZ250 24PPE+PSSABIC Noryl FE8000S 25PPE+PSSABIC Noryl FN150X 26PPE+PSSABIC Noryl FN170X 27PPE+PSSABIC Noryl FN215X 28PPE+PSSABIC Noryl FP6130 29PPE+PSSABIC Noryl FXN119BK 30PPE+PSSABIC Noryl FXN119LG 31PPE+PSSABIC Noryl FXN121BK 32PPE+PSSABIC Noryl FXN121LG 33PPE+PSSABIC Noryl FXN2090H

SABIC Innovative Plastics NORYL EM7100 PPE+PS 物性表

物理性能 额定值 (公制) 额定值 (英制) 测试方法 1.04 g/cc

吸水率 0.10 %

@Time 86400 sec

线性成型收缩率,Flow	0.0050 - 0.0070 cm/cm
	@Thickness 3.20 mm
机械性能额定值 (公制)额定值 (英制)测试方法	41.0 MPa
伸长率 (断裂)	48 %
弯曲强度	62.0 MPa
弯曲模量	2.20 GPa
悬壁梁缺口冲击强度	3.47 J/cm
	1.60 J/cm
	@Temperature -40.0 ° C
落锤总能量	30.0 J
	11.0 J
	@Temperature -30.0 ° C

热膨胀系数(英制)测试方法

73.8 m/m- ° C

@Temperature 0.000 - 100 ° C

载荷下热变形温度(0.46 MPa)

101 ° C

@Thickness 6.40 mm

载荷下热变形温度(1.8 MPa)

98.0 ° C

@Thickness 6.40 mm