

EVAE180F.EVAE180F.EVAE180F.EVAE180F

产品名称	EVAE180F.EVAE180F.EVAE180F.EVAE180F
公司名称	东莞市樟木头富临塑胶贸易商行
价格	18.00/KG
规格参数	
公司地址	东莞市樟木头塑胶市场
联系电话	0769-87705006 13423449117

产品详情

EVAE180F.EVAE180F.EVAE180F.EVAE180F

EVAE180F,鞋材发泡料E180F

Hanwha Total PE E180F 物性表

由 Hanwha Total Petrochemical Co., Ltd. 提供

[下载PDF](#)

[MSDS](#)

General
Material Status

已商用：当前有效
资料 1

Technical Datasheet (English)
[搜索 UL 黄卡](#)

Hanwha Total Petrochemical Co., Ltd.
Availability

北美洲 亚太地区

Features

Good Compression Set 共聚物 可发泡性能 可交联 良好的加工性能 良好的撕裂强度
Uses

泡沫 鞋类
Hardness

额定值

单位制

测试方法
Durometer Hardness
邵氏 A

92

ASTM D2240
邵氏 D

38

Product Description

Description E180F is EVA resin for crosslinked foam applications including mid-sole and in-sole of athletic shoes. This grade is a foaming agent. Characteristics E180F offers good processability during compounding with various additives. Foamed product set properties. Applications Athletic shoe mid-soles and in-soles, Sandals, Cushion padding

Thermal
Brittleness Temperature

< -70

ASTM D746
Vicat Softening Temperature

64.0

ASTM D1525
Melting Temperature

86.0

Internal Method
Physical
Density

0.940

g/cm

ASTM D1505

Melt Mass-Flow Rate (MFR) (190 ° C/2.16 kg)

2.0

g/10 min

ASTM D1238

Vinyl Acetate Content

18.0

wt%

Mechanical

Tensile Strength (断裂)

25.5

MPa

ASTM D638

Tensile Elongation (断裂)

750

%

备注