

防水焊锡环热缩中接管（125 ）

产品名称	防水焊锡环热缩中接管（125 ）
公司名称	广东益联电子科技有限公司
价格	.00/个
规格参数	
公司地址	东升镇胜龙村祥胜路一巷28号
联系电话	18938757244

产品详情

防水焊锡环热缩中接管（125 ）

应用

专为导线连接、焊锡热缩保护、防水一次完成设计的产品。

One piece design , it consists of transparent heat shrinkable sleeve and fluxed solder.

Provides insulation sanity and lower the installed cost.Color hot-melt glue on two ends of heat shrinkable tube , it ; s very convenience use the exact wire dimension.

特性

收缩率2 : 1

含热熔胶具防水功能

热熔胶颜色标示适用尺寸

焊锡环设计容易施工Characteristics

Shrinking ratio2:1

Waterproof for wiring splices

Transparent sleeve provides precise inspection

Easy control soldering process

操作温度范围

工作温度: -55 ~125

开始收缩温度:80

焊锡开始熔解温度 : 111

焊锡完全熔解温度 : 125

Operating temperature range

Operating temperature : -55 ~ 125 Minimum shrink temperature : 80C Minimum fully recovery temperature : 111C

Starting temperature of solder melt : 125C

性能参数 Technical Indicators

MAX operating Temperature	-55 ~ +125
Shrinking temperature	>160
Dielectric strength	1 kV

产品规格 Product Dimensions

Part Number	Product Dimensions (mm)	Wire Dimensions	Cable Size	co

	A(min.)	L(min.)	B(min.)	B & C (max.)	C(min.)	A.W.G(mm)		
YLT-S11	1.7	26	1.0	1.7	0.76	26-24 (0.25-0.34)		Wh
YLT--S21	2.7	40	1.4	2.7	1.2	22-18 (0.5-1.0)		R
YLT--S31	4.5	2.3	4.5	2.0	16-14 (1.5-2.5)		Blue	
YLT--S41	6.0	3.7	6.0	3.4	12-10 (4.0-6.0)		Yellow	
YLT--S31-2	7.3	30	3.8	7.3	3.5			
YLT--S31-3	11.5	34	5.8	11.5	5.5	10-6 (6.0-14.0)		
YLT--S31-9	14.0	47	7.0	14.0	6.8	8-4 (8.0-22.0)		
YLT--S31-8	18.0	56	9.3	18.0	8.8	2-0 (70)		

热收缩套管 Heat shrinkable tubing

低温焊锡环 Low temperature solder sleeve

防水热熔胶 Waterproof hot melt adhesive