

SERENYS PATE CUIVRE

产品名称	SERENYS PATE CUIVRE
公司名称	上海恩莱保贸易有限公司
价格	.00/个
规格参数	
公司地址	上海市松江区金高路2388号813室
联系电话	86-021-20228098 13391171050

产品详情

应用场合：螺纹组件，螺母和螺栓承受非常高的温度。模具顶针。铝挤压（模具修整之前）。扎马克脱模。蒸汽连接和填料函。机械密封件和Orings。包装密封件的浸渍。Applications：Threaded assemblies, nuts and bolts subjected to very high temperatures. Die ejector pins. Aluminum extrusion (prior to mold dressing). Zamak demolding. Steam connections and stuffing boxes. Mechanical seals and Orings. Impregnation of packing seals. Plain bearings on hot bending machines. Hotblast valves. Combustion engines and turbines. Compressors and gas generators. Vulcanizing mold closures. Ingot tongs. Truck center plates and brake calipers. Lubrication of cables and hot chains. Spotwelding machine jaws. Features：Synthetic / Copper powder / Gray / Load = 4800 N / Service temperature range: -20 ° C to +1100 ° C (-4 ° F to +2012 ° F) Property：Synthetic oil-based assembly paste adhesive filled with copper powder. Usable at temperatures ranging from -20 ° C to +1100 ° C (-4 ° F to +2012 ° F). It is applied as a thin film. Without metallic salts (lead) or nitrites. Excellent shelf life under static conditions and when exposed to vibrations. Allows easy part mounting and assembly. Facilitates non-destructive dismantling of parts exposed to high temperatures or corrosive environments. Prevents fretting and resists extreme loads.