

公称压力Nominal pressure	PN
壳体试验Casing test	1.5XPN
密封试验Leak test	1.1XPN
工作温度Operating temperature	橡胶 80 四氟密封 180 硬密封 425 Rubber 80 , PTFE 180 , hard sealing 425
适用介质Working medium	纸浆、污水、煤煤气等paper pulp, sewage, coal slurry

DMZ73Y-10P????????????????????????????????????Profile and connection
dimension Unit:mm

公称压力Nominal pressure (MPa)	公称通径Nominal through diameter (mm)	L	D	D1	D2	H	N-M	D0	
1.0	150	70	280	240	210	475	8-M20	280	
	200	80	335	295	265	540	8-M20	360	
	250	85	390	350	320	630	12-M20	360	
	300	100	440	400	368	480	12-M20	400	
	350	100	500	460	428	885	16-M20	400	
	400	110	565	515	782	990	16-M22	400	
	450	120	615	565	532	1100	20-M22	530	
	500	130	670	620	585	1200	20-M22	530	
	600	140	780	725	685	1450	20-M27	600	
	700	165	895	840	800	1700	24-M27	600	
	800	190	1010	950	905	2000	24-M30	680	
	900	200	1110	1050	1005	2300	28-M30	680	
	1000			1220	1160	1150	2780	28-M33	配电动Electric type optional
	1200			1450	1380	1325	3360	32-M36	
1400			1675	1590	1525	3920	36-M39		
1600			1915	1820	1750	4480	40-M45		