

LEOCH理士电池| LEOCH理士蓄电池Co., Ltd

产品名称	LEOCH理士电池 LEOCH理士蓄电池Co., Ltd
公司名称	浙江兴誉电子科技有限公司
价格	.00/节
规格参数	
公司地址	义乌市北苑街道丹西北路
联系电话	400-070-5861 15066658437

产品详情

LEOCH理士电池| LEOCH理士蓄电池Co., Ltd

理士蓄电池始于1999年，是专门从事LEOCH(理士)牌全系列铅酸蓄电池的研制、开发、制作和出售的世界化新式高科技公司,香港主板上市公司(理士国际00842.HK)。通过多年生长，已变成我国的铅酸蓄电池制作商及的铅酸蓄电池出口商。

理士蓄电池在实践中不断开拓立异、尽力进步。在品质操控上，树立专业的质量管理中心。成功通过了ISO9001、TS16949、ISO14001、OHSAS18001等一系列认证;理士公司与国外闻名电池公司进行了多项技能协作，引入国内外先进设备和仪器，具有多项专利技能，制作才能达到了世界先进水平。并与国内闻名高校进行继续地技能交流协作，树立产学研基地，进步公司自主立异才能，为公司提前变成全球化的，有竞争力的蓄电池领军制作商，奠定了坚实的根底。

产品特性

- 1、高容量高能量密度
- 2、自放电低，较好的容量储存
- 3、板栅采用铅钙合金，水损耗小实现免维护
- 4、高导电性端子，有利于电池大电流放电
- 5、独特的阀控设计，使用安全可靠

6、特殊的板栅设计及铅膏配方，提高电池充电接受能力

7、采用胶体电解液，防止使用过程中电解液分层

The battery contains corrosive liquid, which belongs to dangerous goods. If the transportation safety cannot be ensured, logistics and express delivery will not be provided for the time being. Please contact us before placing an order.

, handling, storage, charging and maintenance:

1. The battery is heavy and its shell is brittle. It should be handled with care and the voltage should be placed upright. It is strictly forbidden to put on the side, roll and throw, and pay attention not to force the terminal.

2. The storage battery should be stored or installed in a dry and ventilated place, away from direct sunlight, away from heat sources and places prone to spark.

3. The storage battery should be fully charged before storage, and it is not allowed to store after discharging. The storage battery should be stored in the environment of 0 ~ 30 , and the storage battery should be supplemented once every two months. The battery pack shall be inspected on a monthly basis. The inspection items are as follows:

(1) The shell and upper cover of the battery shall be kept clean, and the sealing cover bolt and exhaust hole of the battery shall be kept unblocked.

(2) The temperature of the shell and the pole of the battery.

理士阀控式铅酸蓄电池：

1、安全性能好：正常使用下无电解液漏出，无电池膨胀及破裂。

2、放电性能好：放电电压平稳，放电平台平缓。

3、耐震动性好：完全充电状态的电池完全固定，以4mm的振幅，16.7HZ的频率震动1小时，无漏液，无电池膨胀及破裂，开路电压正常。

4、耐冲击性好：完全充电状态的电池从20CM高处自然落至1CM厚的硬木板上3次无漏液，无电池膨胀及破裂，开路电压正常。

5、耐过放电性好：25摄氏度，完全充电状态的电池进行定电阻放电3星期（电阻只相当于该电池1CA放电要求的电阻），恢复容量在75%以上。

6、耐充电性好：25摄氏度，完全充电状态的电池0.1CA充电48小时，无漏液，无电池膨胀及破裂，开路电压正常，容量维持率在上95%以。

7、耐大电流性好：完全充电状态的电池2CA放电5分钟或10CA放电5秒钟。无导电部分熔断，无外观变形。

企业文化：

敢为人先、励精图治、奉献社会"是公司十年艰苦创业实践的写照和升华。

“追求”是一种奋发有为的竞争精神；

“敢为人先”是一种藐视任何艰难险阻的大无畏气度；

“励精图治”是一种瞄准目标，追求有效治理的志向；

“奉献社会”则是我公司对社会的一种承诺。