

深孔枪钻加工油，深孔枪钻油

产品名称	深孔枪钻加工油，深孔枪钻油
公司名称	惠州市嘉沃润滑油有限公司
价格	.00/个
规格参数	品牌:嘉威奥 型号:C-1800 产地:中国
公司地址	惠州仲恺高新区陈江甲子路光明街12号3楼
联系电话	18129639559

产品详情

深孔枪钻加工油，深孔枪钻油

本产品针对深孔枪钻加工的特点，采用国内先进配方，以合成油精制矿物油为基础，添加多种功能添加剂，用特殊生产工艺精制而成。

This product for deep hole gun drill processing, using the domestic advanced formula, using synthetic oil refined mineral oil as base, adding a variety of functional additives, special production process and refined

产品特性：

- 1.安全性好，对人和环境无不良影响。
- 2.优良的防锈性、润滑性和极压性，加工精度高。
- 3.本品含有高渗透性润滑剂，降低摩擦阻力及操作负荷。
- 4.延长刀模具的使用寿命，减少枪钻头磨损断裂。
- 5.粘度合适且长时间保持不变，挥发性小，稳定性高。
- 6.油品流动性好，排屑快，清洗性好。
- 7.油品抗气雾性能优良，油料消耗较少，使用成本较低。

Products characteristics:

good safety, no adverse effects on people and the environment. antirust, lubrication and extreme pressure, high precision machining. This product contains high permeability lubricant, reducing friction and the operating load. extend knife die life, reduce the gun drill wear fracture. suitable viscosity and long time constant, low volatility, high stability. oil has good fluidity, fast chip removal, cleaning and good. The excellent performance of anti fog oil, fuel consumption is less, the use of low cost

产品用途：适用于碳钢、铸铁等各种材质工件的深孔枪钻加工。

Product use: machining deep hole gun is applicable to stainless steel, aluminum alloy, steel, cast iron and other materials of drilling, deep hole boring of workpiece.

技术指标(qualification):

项目 (project item)	质量指标 (qualitative index)	试验方法 (experimental method)
外观 (exterior)	琥珀色液体(Amber liquid)	目测 (visualization)
运动粘度 (kinematic viscosity) mm ² /2、 40	13~16	GB/T265
闪点开口(Flash point opening)/	150	GB/T267
腐蚀/钢片 (Corrosion / steel sheet) 50 , 3h	合格 (qualified)	GB/T378

注意事项：密封储存，防止日晒、雨淋或混入杂质，严禁与其他油品混用。

包装及储运：200升国标桶包装，净重170公斤/桶。

Note: sealed storage, to prevent the sun, rain or impurities, is strictly prohibited and other oil mixture.

Packing and storage: 200 liters GB drum, net weight 170 kg / barrel.