

德国普尔世开关电源-top|现货供应

产品名称	德国普尔世开关电源-top 现货供应
公司名称	昆山照动贸易有限公司
价格	1200.00/台
规格参数	品牌:普尔世 型号:PIM90.245 产地:日本原装进口
公司地址	花桥镇花安路1赛格电子市场3C03号
联系电话	15962635247

产品详情

订货号

DC 输出范围功率输入规格宽x高x深 (mm)特殊特性NEWCP5.12112V10A12-15Vdc120WAC 100-240V | DC
110-150V32124102NEWCP5.24124V5A24-28Vdc120WAC 100-240V | DC
110-150V32124102NEWCP5.241-C124V5A24-28Vdc120WAC 100-240V | DC
110-150V32124102保护面漆NEWCP5.241-M124V5A24-28Vdc120WAC
100-240V32124102NEWCP5.241-S124V5A24-28Vdc120WAC 100-240V | DC
110-150V32124102弹压式接线端子NEWCP5.241-S224V5A24-28Vdc120WAC 100-240V | DC
110-150V32124102直插式接线端子NEWCP5.24224V5A24-28Vdc120WAC 100-240V | DC
110-300V32124102增强直流输入NEWCP5.48148V2.5A48-56Vdc120WAC 100-240V | DC
110-150V32124102Screw terminalsCP10.12112V16A12-15Vdc192WAC 100-240V | DC
110-150V39124117NEWCP10.12212V16A12-15Vdc192WAC 100-240V | DC
110-300V39124117增强型直流输入CP10.24124V10A24-28Vdc240WAC 100-240V | DC
110-150V39124117CP10.241-C124V10A24-28Vdc240WAC 100-240V | DC
110-150V39124117保护面漆CP10.241-M124V10A24-28Vdc240WAC 100-240V | DC
110-150V39124117批准用于医疗应用CP10.241-S124V10A24-28Vdc240WAC 100-240V | DC
110-150V39124117弹压式接线端子NEWCP10.241-S224V10A24-28Vdc240WAC 100-240V | DC
110-150V39124117直插式接线端子NEWCP10.24224V10A24-28Vdc240WAC 100-240V | DC
110-300V39124117增强型直流输入CP10.36136V6.7A36-42Vdc240WAC 100-240V | DC
110-150V39124117CP10.48148V5.4A48-56Vdc260WAC 100-240V | DC
110-150V39124117NEWCP20.24124V20A24-28Vdc480WAC 100-240V | DC
110-150V48124127NEWCP20.241-C124V20A24-28Vdc480WAC 100-240V | DC
110-150V48124127敷形涂层NEWCP20.241-S124V20A24-28Vdc480WAC 100-240V | DC
110-150V48124127弹压式接线端子NEWCP20.241-S224V20A24-28Vdc480WAC 100-240V | DC
110-150V48124127直插式接线端子NEWCP20.241-V124V20A24-28Vdc480WAC 100-240V | DC

110-150V48124127远程关断NEWCP20.24224V20A24-28Vdc480WAC 100-240V | DC
110-300V48124127增强型直流输入NEWCP20.24824V20A24-28Vdc480WAC 100-240V | DC
110-150V48124127Monitoring displayNEWCP20.48148V10A48-56Vdc480WAC 100-240V | DC
110-150V48124127CPS20.12112V30A12-15Vdc405WAC 100-240V65124127CPS20.24124V20A24-28Vdc480WAC
100-240V65124127CPS20.241-C124V20A24-28Vdc480WAC
100-240V65124127保护面漆CPS20.36136V13.3A36-42Vdc480WAC
100-240V65124127CPS20.48148V10A48-56Vdc480WAC 100-240V65124127CS3.24124V3.3A24-28Vdc80WAC
100-240V | DC 110-300V32124102CS5.24124V5A24-28Vdc120WAC 100-120V AC
200-240V32124117CS5.241-C124V5A24-28Vdc120WAC 100-120V AC
200-240V32124117保护面漆CS5.241-S124V5A24-28Vdc120WAC 100-120V AC
200-240V32124117弹压式接线端子CS5.24324V5A24-28Vdc120WAC
100-120V32124117CS5.24424V5A24-28Vdc120WAC 200-240V32124117CS10.24124V10A24-28Vdc240WAC
100-120V AC 200-240V60124117CS10.241-S124V10A24-28Vdc240WAC 100-120V AC
200-240V60124117弹压式接线端子CS10.24224V10A24-28Vdc240WAC 100-120V AC
200-240V60124117CS10.24324V10A24-28Vdc240WAC 100-120V60124117CS10.24424V10A24-28Vdc240WAC
200-240V60124117CS10.48148V5A48-52Vdc240WAC 100-120V AC
200-240V60124117QS3.24124V3.4A24-28Vdc80WAC 100-240V | DC
110-300V32124102QS5.24124V5A24-28Vdc120WAC 100-240V | DC
110-300V40124117QS5.241-A124V5A24-28Vdc120WAC 100-240V | DC
100-300V40124117敷形涂层覆膜保护，ATEX认证QS10.12112V15A12-15Vdc180WAC 100-240V | DC
110-150V60124117QS10.24124V10A24-28Vdc240WAC 100-240V | DC
110-150V60124117QS10.241-A124V10A24-28Vdc240WAC 100-240V | DC
110-150V60124117敷形涂层覆膜保护，ATEX认证QS10.241-C124V10A24-28Vdc240WAC 100-240V | DC
110-150V60124117保护面漆QS10.241-D124V10A24-28Vdc240WAC 100-240V | DC
110-300V60124117增强直流输入QS10.30130V8A28-32Vdc240WAC 100-240V | DC
110-150V60124117QS10.48148V5A48-56Vdc240WAC 100-240V | DC
110-150V60124117QS10.481-D148V5A48-56Vdc240WAC 100-240V | DC
110-300V60124117增强直流输入QS20.24124V20A24-28Vdc480WAC 100-240V | DC
110-150V82124127QS20.241-A124V20A24-28Vdc480WAC 100-240V | DC
110-150V82124127敷形涂层覆膜保护，ATEX认证QS20.241-C124V20A24-28Vdc480WAC 100-240V | DC
110-150V82124127保护面漆QS20.24424V20A24-28Vdc480WAC
200-240V70124127QS20.36136V13.3A36-42Vdc480WAC 100-240V | DC
110-150V82124127QS20.48148V10A48-55Vdc480WAC 100-240V | DC
110-150V82124127QS40.241-C224V40A24-28Vdc960WAC
100-240V125124127的部分电路板带敷形涂层覆膜QS40.24124V40A24-28Vdc960WAC
100-240V125124127QS40.24424V40A24-28Vdc960WAC
200-240V125124127QS40.36136V26.7A36-42Vdc960WAC
100-240V125124127QS40.48148V20A48-54Vdc960WAC 100-240V125124127QS40.48448V20A48-54Vdc960WAC
200-240V125124127

DIMENSION概念型 | 集成解耦功能的电源

以下单相DIN导轨电源具有集成的解耦功能。通过这一创新，普尔世的用户可以构建无附加冗余模块的冗余系统。

[了解更多](#)

DIMENSION

订货号

DC 输出范围功率输入规格宽x高x深 (mm)特殊特性NEWCP10.241-R124V10A24Vdc240WAC 100-240V | DC
110-150V39124117弹压式接线端子NEWCP10.241-R224V10A24Vdc240WAC 100-240V | DC
110-150V39124117热插拔插头NEWCP10.241-R2-C124V10A24Vdc240WAC 100-240V | DC
110-150V39124117保护面漆NEWCP10.242-R224V10A24Vdc240WAC 100-240V | DC
110-300V39124117可热插拔，增强型直流输入NEWCP20.241-R124V20A24Vdc480WAC 100-240V | DC
110-150V48124127内置冗余，弹压式接线端子NEWCP20.241-R224V20A24Vdc480WAC 100-240V | DC
110-150V48124127可热插拔NEWCP20.245-R224V20A24Vdc480WAC 100-240V | DC
110-150V48124127可热插拔NEWCP20.241-R2-C124V20A24Vdc480WAC 100-240V | DC
110-150V48124127可热插拔 保护面漆NEWCP20.242-R224V20A24Vdc480WAC 100-240V | DC
110-300V48124127可热插拔，增强型直流输入

PIANO比亚诺 | 单相DIN导轨电源

下表列出了我们PIANO比亚诺产品系列的单相电源 -
专注于在提供基本特性前提下的质量：转换效率、使用寿命、可靠性和尺寸。

PIANO

订货号

DC 输出范围功率输入规格宽x高x深 (mm)特殊特性NEWPIM36.24124V1.5A24-28Vdc36WAC 100-240V | DC
24V229091直插式接线端子NEWPIM60.24124V2.5A24-28Vdc60WAC
100-240V369091直插式接线端子NEWPIM60.12112V5A12-15Vdc60WAC
100-240V369091直插式接线端子NEWPIM60.12512V5A12-15Vdc60WAC
100-240V369091大线径螺丝端子NEWPIM60.24524V2.5A24-28Vdc60WAC 100-240V369091Screw
terminalsNEWPIM90.24124V3.8A24-28Vdc90WAC
100-240V369091直插式接线端子NEWPIM90.245-L124V3.8A24-28Vdc90WAC
100-240V369091螺丝端子NEWPIM90.24524V3.8A24-28Vdc90WAC
100-240V369091直插式接线端子PIC120.241C24V5A24-28Vdc120WAC 200-240V39124124DC-
OK继电器触点PIC120.241D24V5A24-28Vdc120WAC 100-120V AC 200-240V39124124DC-
OK继电器触点PIC120.242C24V5A24-28Vdc120WAC
200-240V39124124PIC240.241C24V10A24-28Vdc240WAC 200-240V49124124DC-
OK继电器触点PIC240.241D24V10A24-28Vdc240WAC 100-240V49124124DC-
OK继电器触点NEWPIC480.241C24V20A24-28Vdc480WAC 200-240V49124124DC-
OK继电器触点NEWPIC480.241D24V20A24-28Vdc480WAC 100-240V59124127DC-
OK继电器触点NEWPIC480.481D48V10A48-56Vdc480WAC 100-240V59124127DC-OK继电器触点