

	mpa	m3 / min	kw	db(a)	kg		l / min	mm
gl-08b(f)	0.8	1.1	7.5	58	500			1000 × 640 × 1000
	1.0	1.02						
	1.25	0.81						
gl-11b(f)	0.8	1.5	11	58	540			1000 × 640 × 1000
	1.0	1.32						
	1.25	1.02						
gl-15b(f)	0.8	2.40	15	63	650			1460 × 850 × 1400
	1.0	2.12						
	1.25	1.61						
gl-18b(f)	0.8	3.10	18.5	65	840			1460 × 850 × 1400
	1.0	2.62						
	1.25	2.13						
gl-22b(f)	0.8	3.50	22	65	870			1460 × 850 × 1400
	1.0	3.13						
	1.25	2.61						
gl-30b	0.8	5.00	30	66	980			1550 × 930 × 1620
	1.0	4.20						
	1.25	3.81						
gl-37b	0.8	6.10	37	67	1000			1550 × 930 × 1620
	1.0	5.22						
	1.25	4.81						
gl-45b	0.8	7.30	45	68	1060			1550 × 930 × 1620
	1.0	6.13						
	1.25	5.65						
gl-55b	0.8	9.60	55	70	1250			2300 × 148 0 × 1330
	1.0	8.60						
	1.25	7.42						
gl-75b	0.8	12.50	75	73	1480			2300 × 148 0 × 1330
	1.0	11.42						
	1.25	9.83						
gl-90b	0.8	16.30	90	73	2030			2650 × 122 0 × 1800
	1.0	14.52						
	1.25	12.30						
gl-110b	0.8	19.40	110	78	2450			2650 × 122 0 × 1800
	1.0	16.90						
	1.25	15.10						
gl-132b	0.8	22.00	132	78	2550			2650 × 122

	1.0	20.18						0 × 1800
	1.25	18.12						
gl-160b	0.8		160	78	2710			2300 × 160 0 × 2000
	1.0							
	1.25							
gl-200b	0.8		200	78	4100			3300 × 220 0 × 2000
	1.0							
	1.25							
gl-250b	0.8		250	78	4500			3300 × 220 0 × 2000
	1.0							
	1.25							
· 工作压力为0.9mpa时，排气量略有不同。 · jns系列另有水冷及变频机组，详情请询问本公司。								