

PP RP340R 韩国大林BASELL

产品名称	PP RP340R 韩国大林BASELL
公司名称	浙江昌宏塑胶原料有限公司
价格	.00/个
规格参数	品牌:巴塞尔BASELL 型号:MoplenRP340R 特性:透明, 抗撞击性, 良好
公司地址	义乌市江东街道端头二区58栋1号
联系电话	0579-15868975843 15868975843

产品详情

韩国大林BASELL PP RP340R产品说明：

RP340R是一种高熔体流动速率的无规共聚物。它具有高透明度和光泽，流动性好，硬度/冲击力平衡，气味和风味转移非常低。

应用：

对气味和味道变化敏感的食品包装、化妆品包装、桶和耐用罐、ISBM（注塑拉伸吹塑成型）瓶、透明家居用品。

处理：

注塑成型

Braskem PP RP340R 物性表

基本信息

	良好的流动性	
	无规共聚物	
用途	中等硬度 高光泽 高阻隔性 低的气味转移性 低的味道转移性 食品包装，良好	
机构评级	桶	
外观	FDA 21 CFR 177.1520	
加工方法	清晰/透明 Injection Stretch Blow Molding	
物理性能额定值单位制测试方法	注射成型	0.902
熔流率（熔体流动速率）(230 ° C/2.16 kg)		25
硬度额定值单位制测试方法 R 级, 注塑		84
R 计秤		82
机械性能额定值单位制测试方法 屈服, 注塑		30.0
屈服, 注塑		31.0

伸长率 屈服, 注塑	14
屈服, 注塑	12
弯曲模量 - 1% 正割 注塑	1000
注塑	1100
悬臂梁额定值单位制测试方法 23 ° C, 注塑	50
23 ° C, 注塑	50

热性能额定值单位制测试方法
BraskemPP RP340R

物性介绍：

RP340R is a high melt flow rate random copolymer. It features high transparency and gloss combined with good flowability, good balance of rigidity/impact and very low odor and flavor transfer. Applications: Packages for foods that are sensitive to changes in odor and taste, packages for cosmetics, pails and durable pots, bottles by ISBM (injection stretch blow molding), transparent houseware. Processing: Injection Molding

Braskem PP RP340R

聚丙烯无规共聚物PP RP340R