

# BBK玻璃板液位计代理商

产品名称	BBK玻璃板液位计代理商
公司名称	石家庄仓粒能源科技有限公司
价格	150000.00/台
规格参数	品牌:BBK 材质:CS 温度:300
公司地址	河北省石家庄市长安区跃进路208号银龙南区1-1-501号（注册地址）
联系电话	0311-66562231 17603290771

## 产品详情

BBK玻璃板液位计. 因此它主要用于需要水和蒸汽的锅炉应用中. 由于仪表的两个色彩水平指示出色. remote monitoring can be done by reflection mirror and ducts or ITV monitoring system. SW12系列的开发是为了追随火力或核电站设备向更高压力/温度应用发展的趋势. 以不承受直接的过大拉紧应力负荷. Mirror watching device consisting of reflection mirror and ducts. that comes up with the difference of refraction caused by existence or non-existence of the liquid. Glass Borosilicate Silicon Coated FEP Coated Gasket PTFE Graphite Non-Asbestos Bolt Std. 由于SW6系列是在比SW4系列更高的压力/温度条件下使用的. 从而引起了折射的差异通过液体的存在或不存在. transparent gas and liquid. As SW6 series is used under higher pressure/temperature condition than SW4 series. enable to withstand the heavy tightened load in order to increase the sealing capacity, 材质: ( : 标准 : 选项 : 不适用) Gauge Model SW4 SW6 SW12 Max. 可以通过两种颜色的边界清楚地识别出液体的液位, 旨在实现更高效的发电系统, 透明的气体和液体. 还可以使用由反射镜和管道组成的镜子监视设备以及ITV监视, level of the liquid can be clearly recognized by the boundary of the two colors. Pressure ( NoBBK玻璃板液位计, mounting manner of the gauge is generally an off-set type by means of buffer pipe (expansion). Oper. 因此压力表的安装方式通常是通过缓冲管 (膨胀) 进行偏置的. Application and Features SW4 series is used mainly for steam services under low to medium pressure, 应用与特点 SW4系列主要用于低压至中压的蒸汽服务. there are direct mount by use of a buffer pipe (called Expansion pipe) which is to absorb the thermal shock of the gauge under the high temperature operation BBK玻璃板液位计, it is mostly used for boiler applications which are worked with water and steam, 为了将量规安装在滚筒上. W6 series is the standard two-color level gauge for medium and high pressure steam services. 借助两个彩色照明器, For mounting manner of the gauge on the drum, 5(157) Temp BBK玻璃板液位计. Material: ( : Standard : Option : Not Applicable) 日本BBK公司 两色透明液位计 SW4 ? SW6 ? SW12 摘要 这种类型的量规主体在其横截面图中由梯形形成, 因此可以清晰地进行远程水平监测, and ITV monitoring are also applicable. Since the gauge of this type is functional only with clear, 可以通过反射镜和风道或ITV监视系统进行远程监视. 以便当透明液体与相对的两个玻璃接触时形成棱镜. 可以使用缓冲管 (称为膨胀管) 直接安装, SW12 series was developed to follow up the tendency of thermal or nuclear power plant equipments toward higher pressure/temperature applications aiming at more highly efficient power generating system.

The gauge glasses are being embedded in cover so as to receive no direct excessive load of tightening stress, Hard Stl  
Stainless Stl.4 glass used ) Unit : MPa(kgf/cm<sup>2</sup>) 10BBK玻璃板液位计. Range ( ) -10 ~ 450 -10 ~ 450  
-10 ~ 450 Mat'l Gauge Body Carbon Stl Stainless Stl,能够承受沉重的拉紧负荷以增加密封能力.通过这  
种设计并借助于安装在量规后部的照明器以提供红色和绿色的光.8(110) 11BBK玻璃板液位计,该模型已在  
世界范围内用于高压蒸汽鼓和焚烧发电厂.由于这种压力表仅适用于透明.日本BBK公司 两色透明液位计  
Two-ColorTransparent Type Liquid Level Gauge 两色透明液位计 SW4 ? SW6 ? SW12 Summary Gauge body of  
this type is formed of a trapezoid in its cross sectional view so as to form a prism when a clear liquid comes in contact  
with opposing two glasses,量规玻璃被埋入盖子中.4(116) 15. Remote level monitoring can be done clearly owing to  
brilliant two color level indication of the gauge, SW6系列是用于中高压蒸汽服务的标准两色液位计, With this  
devising and with the aid of an illuminator installed at the rear of the gauge to provide with red and green lights. With  
the aid of two color illuminatorBBK玻璃板液位计,该缓冲管用于吸收在高温操作下量规的热冲击, Great  
number of the model has been used for the high pressure steam drums and the incineration power plants in the world  
BBK玻璃板液位计.