

# 专业生产数控精雕机，电脑雕刻机

产品名称	专业生产数控精雕机，电脑雕刻机
公司名称	常州金奇雕数控机床有限公司
价格	.00/个
规格参数	品牌:JQD 型号:JQD-45M 主电机功率:1.5-2.2 ( kw )
公司地址	武进区湖塘镇沟南村
联系电话	13601503286

## 产品详情

品牌	JQD	型号	JQD-45M
主电机功率	1.5-2.2 ( kw )	主轴转速范围	5000-24000 ( rpm )
工作形式	其他	布局形式	立式
动力类型	机械传动	用途	高频模、滴塑模，中、小型模具的雕铣加工、定位打孔、鞋模制作、汽车零部件加工
适用范围	通用	适用行业	通用
产品类型	全新	是否库存	否

4

jqd-45m金奇雕cnc雕刻机（伺服）jqd-45mjinqidiao cnc engraver(servo)

特点及应用characteristics and application:

jqd-45m整机底座采用铸造件，钢性强，稳定性好；精密直线矩形导轨，有预紧，钢性好，精度

高；研磨级精密滚珠丝杆有预紧，精度高；接口采用国际标准g代码指令，兼容国内外雕刻软件，操作实用简便。主要适用高频模、滴塑模，中、小型模具的雕铣加工、定位打孔、鞋模制作、汽车零部件加工及电子零部件加工。

the main frame of jqd-45m adopts castings to structure a case-type base with strong rigidity and good stability. the precision straight guide rail has pretension, good rigidity and high accuracy. the grinding grade precision ball guide screw has pretension and high accuracy. the interface adopts international standard g code instructions which is compatible with domestic and foreign engraving software and is easily and conveniently operated. it is mainly suitable for high frequency mould, plastic dropping mould, engraving and milling of medium and small moulds, positioning and hole drilling, manufacturing of shoe moulds, processing of parts and components of automobile as well as electronic parts and components.

工作台尺寸 sizes of worktable	480 × 380mm
x、y、z轴工作行程 work strokes of x、y、z axes	450 × 400 × 110mm
x、y、z轴定位精度 positioning accuracy of x、y、z axes	± 0.01/300mm
x、y、z轴重复定位精度 repeat positioning accuracy of x、y、z axes	± 0.01mm
工作台平面度 evenness of worktable	± 0.025/300mm
x、y垂直度 verticality of worktable	0.025/300mm
z向空间高度 spatial height in z direction	280mm
主轴功率 power of spindle	1.5-2.2kw
主轴转速 speed of spindle	5000-24000rpm
驱动系统 driving system	伺服 servo
工作电压 work voltage	单相 220v 50hz ± 10% single phase 220v 50hz ± 10%
机床重量 weight of machine tool	1000kg
机床外形尺寸 outline sizes machine tool	1180 × 1200 × 1750mm