

超静音，数控式连续剥皮，剥带打端子机

产品名称	超静音，数控式连续剥皮，剥带打端子机
公司名称	苏州市吴中区用直毅高机械配件经营部
价格	.00/个
规格参数	品牌:江苏益高 型号:YG-1.8TS 用途:电线剥皮端子压着一个动作
公司地址	中国 江苏 苏州市吴中区 用直长虹南路268号
联系电话	00852 0512 65023015 13806212636

产品详情

品牌	江苏益高	型号	YG-1.8TS
用途	电线剥皮端子压着一个动作	别名	剥皮带打端子机

电线剥皮及端子压着一个动作完成。卡式模座和剥皮系统的组合使机台达到连贯动作。剥皮系统采用步进电机驱动，瞬间启动能产生高扭矩效果。剥皮系统设计有自动、手动及自动回位等功能。待机时间可调整：可视线材及端子需求而来调整，端子铆合完成之后，剥皮座回位之时间。使用凸输方式完成剥皮及进刀深度，稳定性高。端子铆合松紧度可由机台上方微调旋转调整，调整精度每格 0.02mm。有抽取线皮屑及退料装置之设计

explanation of features the wire stripping and terminal pressing are completely together. the combination of cassette mold seat and stripping system can manage continuous operation. the stripping system adopts stepping motor driving, and the instant starting can produce effect of high torque. the stripping system has the functions of automatic return, manual return, and automatic return, etc. the stand-by time can be adjusted. adjust the return time of stripping seat after terminal riveting according to requirements of wire material and terminal. manage stripping and cutting depth through convex transmission, to ensure high stability. the terminal riveting tension can be adjusted through rotation of upper part of the machine, with the adjustment precision of 0.02mm/grade. it can draw wire waste and returning equipment. 技术参数 technical

型号	parameter model	yg-1.8ts
作业能力	work capacity	电线的剥皮以及端子压著的连贯作业 uninterrupted wire stripping and terminal pressing
电源	power	ac 110/220v 50hz/60hz 单相 ac 110/220v 50hz/60hz single-phase
马达	motor	端子机1/3hp 剥皮部分步进马达 40w terminal machine 1/3hp; stepping motor in stripping part: 40w
控制方式	control mode	可自动剥皮打端子、可单独压

		端子、可单独剥皮 it can manage automatic stripping and terminal pressing, separate terminal pressing and separate stripping.
能力	capacity	1.8ton
冲程	stroke	30mm
剥皮长度	stripping length	2--6mm
空气压力	air pressure	5--8kgf(需使用清洁干燥空气) 5-8kgf (need clean and dry air)
外观尺寸	external dimensions	440x500x2800mm
重量	weight	90kg