



t04	4 × 95/32	0 ~ 1.0 ( 0 ~ 10 )	7.7(77)	7	100	约5倍	绕线轴样式	透明蓝色带影像线	
t06	6 × 111/4	0 ~ 1.0 ( 0 ~ 10 )	7.3(73)	9	100				
t08	8 × 13.55/16	0 ~ 1.0 ( 0 ~ 10 )	5.5(55)	13	100				
t09	9 × 153/8	0 ~ 1.0 ( 0 ~ 10 )	5.0(50)	15	100				
t10	10 × 1613/32	0 ~ 1.0 ( 0 ~ 10 )	5.0(50)	16	100				
t12	12 × 181/2	0 ~ 0.8 ( 0 ~ 8 )	5.0(50)	19	100				
t15	15 × 225/8	0 ~ 0.8 ( 0 ~ 8 )	4.0(40)	27	100				
t19	19 × 263/4	0 ~ 0.6 ( 0 ~ 6 )	3.8(38)	16	50				
t22	21.5 × 2927/32	0 ~ 0.6 ( 0 ~ 6 )	3.5(35)	20	50				约6倍
t25	25 × 331	0 ~ 0.6 ( 0 ~ 6 )	3.0(30)	25	50				
t32	32 × 411-1/4	0 ~ 0.4 ( 0 ~ 4 )	2.3(23)	35	50				
t38	38 × 481-1/2	0 ~ 0.4 ( 0 ~ 4 )	1.9(19)	45	50				约9倍
t45	45 × 561-3/4	0 ~ 0.4 ( 0 ~ 4 )	1.7(17)	48	40				
t50	50 × 622	0 ~ 0.3 ( 0 ~ 3 )	1.5(15)	54	40				
t63	63 × 802-1/2	0 ~ 0.3 ( 0 ~ 3 )	1.3(13)	53	20				
t75	75 × 923	0 ~ 0.3 ( 0 ~ 3 )	1.2(12)	62	20				

\* 工作温度范围:-5 ~ 60