

# 轿厢复式升降电梯

产品名称	轿厢复式升降电梯
公司名称	河南快创机械设备有限公司
价格	.00/个
规格参数	河南快创:商丘市 复式B150:具体参数介绍内参照 上海市:浦东新区
公司地址	商丘市睢阳区神火大道与北海路交叉口西北角企业中心5楼502-2
联系电话	03707934828

## 产品详情

### 复式升降机《duplex lift》-B150 技术参数

安装环境Installation environment	室内Indoor
安装方式Installation	无基坑安装, 高80MM No foundation pit installation, high 80MM
安装空间installation space	1030X860MM
外形尺寸outline dimension	1010X800MM
平台尺寸Platform size	700X720MM
顶层高度Top level	2300MM
停层站 Stop Station	小于等于2层站Maximum 2-storey station
高度maximum altitude	小于等于12米Maximum 13m
标准层高Standard level	标准层高3.5米/每层 Standard layer 3.5 m high/per layer
出入方向 Access directions	180 ° 贯通/ 90 ° /或原进原出 180 ° through /90 ° / or original in / out
电源power	1.5KW/AC220V/50HZ家用 (domestic)
驱动方式Driving mode	液压驱动hydraulic pressure
运行速度running speed	80-120MM/秒100MM/sec
层门控制gate control	手动+闭门器 Manual door closers
控制方式control method	点动 按住运行/自动Click Hold down run / auto
轿厢侧板Car side	5+5钢化夹胶玻璃或铝板喷塑 5+5 toughened with glue glass or aluminum
轿厢门 Car door	5MM钢化玻璃5MM tempered glass
控制电压control voltage	24V/DC

整机颜色Machine color	标准色：白色（可选）Standard Color: White (optional)
承重Maximum load bearing	小于等于250KG/350KG
设备噪音noise	小于60dB Less than 60 dB
工作温度working temperature	-5C ° / +40C °
安全装置 safety device	<p>* 手动应急下降及开门装置</p> <p>Manual emergency drop and door opening device</p> <p>* 平台主控面板优先</p> <p>Platform master panel preferred</p> <p>* 紧急停止按钮 Emergency stop button</p> <p>* 轿门与设备联动控制</p> <p>Car door and equipment linkage control</p> <p>* 轿厢底部防撞Car bottom collision</p> <p>* 轿厢顶部防撞 Car roof collision</p> <p>* 防坠落机械装置 anti-fall mechanical device</p> <p>* 电控系统防过流过载保护</p> <p>Electronic control system to prevent overcurrentoverload protection</p> <p>* 平台超重保护 Platform Overweight Protection</p> <p>* 液压油路防爆阀</p> <p>Hydraulic oil circuit explosion-proof valve</p>