

进口绝缘保温材料低温台车箱式回火炉

| | |
|------|------------------------------|
| 产品名称 | 进口绝缘保温材料低温台车箱式回火炉 |
| 公司名称 | 苏州热优贸易有限公司 |
| 价格 | .00/个 |
| 规格参数 | 品牌:捷克LAC 型号:SVK 别名:回火炉 |
| 公司地址 | 苏州工业园区和顺路1号博济生能科技园210室 |
| 联系电话 | 0512-87186613 13912619019 |

产品详情

| | | | |
|--------|----------|-------|--|
| 品牌 | 捷克LAC | 型号 | SVK |
| 别名 | 回火炉 | 适用范围 | 低温台车箱式炉适用于干燥、硫化、表层塑化、粒化烘干、电器元件干燥及加工过程前预热各种材料、材料深层加热等，如人工老化铝制品；还可以应用于塑料、橡胶、铸造工业 |
| 炉膛最高温度 | 450 () | 工作温度 | 450 () |
| 装载量 | - (kg) | 工作室尺寸 | - (mm) |
| 外形尺寸 | - (mm) | 类型 | 台车炉 |

low-temperature bogie-hearth chamber furnaces and d

低温台车箱式炉svk

application

应用范围：

svk bogie-hearth chamber dryers and low-temperature furnaces are suitable for drying, vulcanisation, curing of surface layers, granulate drying, burning-in of electrical components and preheating of various materials before additional processing and further for heat treatment of material such as artificial ageing of aluminium and its alloys and other materials, if applicable, primarily in plastics, rubber, automotive, electrotechnical, glass, ceramic and foundry industry. behalf its design they provide for comfortable loading of bulky and heavy batches into the furnace using a crane or other method.

低温台车箱式炉适用于热各种材料、材料深、电镀技术、玻璃、而重的原料。

结构描述：

· 熔炉框架、炉门及

description of dryer construction:

-frame, door and outer jacket is made of special insulation sandwich plates connected by thin-walled steel sections

-the door opens upwards electrohydraulically

-venting and suction bleeder is located on central fan unit

-the internal air circulation is horizontal and is solved by means of central circulation unit containing also heating elements (for all dryer sizes)

-switchboard is on the right side of the dryer

-industry controller enables to save 30 control programs, each program may include up to 15 steps; the operator may start the selected program on specified date and hour by means of real-time clock

-heating switched off by end switch when the door opens

-k-type thermocouple, contactless switch relay, limit unit ht 40b

standard equipment of dryer includes:

-manually controlled flap,

-industry controller with limit unit ht 40b,

-rails,

-3 ammeters on switchboard

-calibration of the entry of the measuring controller

-we offer the following accessories for extra charge:

-bogie with electric drying unit

-another manually or electrically-driven bogie

-loading frame with shelves

-second door, inspection hole in the door

-automatic venting flap

-exhaust fan for outlet

-modification for vertical circulation of atmosphere in the furnace

-rs 232 or eia 485 interface to connect the controller to pc, software for record and monitoring of temperature cycle

· 水压上开门

· 通风抽气分压器置

· 水平空气内循环有

· 工业控制器的内部
以按照安装的实时钟

· 炉门打开时，终止

· k型热电偶，非接

优点：

· 抗机械阻力及抗腐

· 中央供热系统及风

· 中央供热与风扇系

· 顶级绝缘材料，摸

· 干燥器结构可以用

额外收费附件：

· 电动推车

· 带架子的装载结构

· 自动通风孔

· 出口处通风扇

· 炉内竖向空气循环

· 监控并记录温度循

· 图表温度记录器

· 相关湿度测量

· metrex气瓶

· 减少或增大熔炉功

· 间接燃气供热

标准设计包括：

-graphic temperature recorder

-relative humidity measurement

-metrex gas analyser

-furnace power reduction or increase

-indirect gas heating

benefits:

-dryer chamber with long life, mechanical resistance and corrosion resistance

-circulation of internal atmosphere provides for even temperature distribution in internal volume of the dryer

-central heating and fan unit

-high-quality insulation material results in low operating costs

-the dryer construction allows for comfortable loading of bulky and heavy batches, e.g. using a crane

· 手动通风孔

· 带极限装置的工业

· 围栏

· 配电盘配有三只电

可选型号：

| 类型lac | 最高温度 | 容积l | 外部尺寸(w × h × d)mm | 内部尺寸(w × h × d)mm | 电 |
|-------------|------|------|--------------------|--------------------|---|
| svk 1000/25 | 250 | 1020 | 1600 × 2400 × 1650 | 900 × 900 × 1260 | 3 |
| svk 1500/25 | 250 | 1500 | 1800 × 2500 × 1900 | 1000 × 1000 × 1500 | 3 |
| svk 2000/25 | 250 | 2000 | 1800 × 2500 × 2400 | 1000 × 1000 × 2000 | 3 |
| svk 3600/25 | 250 | 3600 | 2100 × 2900 × 2900 | 1200 × 1200 × 2500 | 3 |
| svk 4500/25 | 250 | 4330 | 2100 × 2900 × 3400 | 1200 × 1200 × 3000 | 3 |
| svk 7200/25 | 250 | 7200 | 2400 × 3600 × 3400 | 1500 × 1600 × 3000 | 3 |
| svk 1000/45 | 450 | 1020 | 1600 × 2400 × 1650 | 900 × 900 × 1260 | 3 |
| svk 1500/45 | 450 | 1500 | 1800 × 2500 × 1900 | 1000 × 1000 × 1500 | 3 |
| svk 2000/45 | 450 | 2000 | 1800 × 2500 × 2400 | 1000 × 1000 × 2000 | 3 |
| svk 3600/45 | 450 | 3600 | 2100 × 2900 × 2900 | 1200 × 1200 × 2500 | 3 |
| svk 4500/45 | 450 | 4300 | 2100 × 2900 × 3400 | 1200 × 1200 × 3000 | 3 |
| svk 7200/45 | 450 | 7200 | 2400 × 3600 × 3400 | 1500 × 1600 × 3000 | 3 |