

# 管式炉 LT LAC 实验室管式炉LT

产品名称	管式炉 LT LAC 实验室管式炉LT
公司名称	苏州热优贸易有限公司
价格	.00/个
规格参数	品牌:LAC 型号:实验室管式炉LT 最大电压:380 ( V )
公司地址	苏州工业园区和顺路1号博济生能科技园210室
联系电话	0512-87186613 13912619019

## 产品详情

品牌	LAC	型号	实验室管式炉 LT
最大电压	380 ( V )	功率	xx ( W )
额定温度	1300 ( )	主要用途	用于特殊试验及研究项目 laboratory tube furnaces lt
管式炉lt			
application	应用范围 :		
special laboratory and research work	用于特殊试验及研究		
description of furnace construction:	结构描述 :		
*frameless construction of bent sheet	· 优质不锈钢外壳,无		
*desktop design	· 桌面设计		
*upper part of the furnace folds up using a handle	· 熔炉上部可用把手		
*heating spirals located in insulation grooves	· 加热旋管设于绝缘		
*insulation consisting of mineral plates forming circular modules	· 绝缘体由矿物盘组		
*wiring located in separate switchboard	· 配线置于独立的配		

\*industry controller enables the saving of 30 control programs, each program may include up to 15 steps; the operator may start the selected program on a specified date and hour using the real-time clock

\*s-type thermocouple

standard equipment of furnace includes:

\*ht 40 controller.

accessories for extra charge:

\*industry controller with rs 232 or rs 485 interface

\*sw set for pc connection in order to monitor and record working cycles

\*graphic temperature recorder

\*protection atmosphere inlet

\*stand for vertical positioning of the furnace

\*various types of tubes

\*tube packer of mineral fibre

\*3-zone heating system for models with tube length 750 mm

benefits:

\*all stainless-steel design

\*premium insulation materials (low electricity consumption, possibility of quick attainment of required temperature)

\*very even temperature distribution at din 17052-1

\*programmable temperature control

\*semi-conductor relay (fluent and noiseless operation, minimum interference with surrounding devices)

\*flawless workshop design, technical equipment and operational safety

· 工业控制器的内部  
以按照安装的实时钟

· s型电热偶

标准设计包括：

· ht 40控制器

优点：

· 完全不锈钢设计

· 价值不菲的绝缘材

· 可编写程序的温度

· 抗干扰半导体继电

· 最佳温度均匀性符

· 完美的车间设计、

额外收费附件：

· 带有rs 232 or rs 485

· 用于电脑连接的一

· 图表温度记录器

· 空气保护入口

· 竖直熔炉时所需的

· 各种型号的管子

· 矿物纤维管子打包

· 为管长为750毫米机

可选型号：

类型	最高 温度	内部 管直径	外部尺寸	
			( 宽高深 ) mm	
lac		mm		
lt 50/300/13	1300	50	570 × 310 × 510	
lt 50/500/13	1300	50	810 × 310 × 510	
lt 50/750/13	1300	50	1100 × 310 × 510	
lt 75/500/13	1300	75	810 × 400 × 600	
lt 75/750/13	1300	75	1100 × 400 × 600	
lt 100/500/13	1300	100	810 × 450 × 650	
lt 100/750/13	1300	100	1100 × 450 × 650	