

煅烧炉 KR LAC 带旋转罐的煅烧炉

产品名称	煅烧炉 KR LAC 带旋转罐的煅烧炉
公司名称	苏州热优贸易有限公司
价格	.00/个
规格参数	品牌:LAC 型号:带旋转罐的煅烧炉 最大电压:220 (V)
公司地址	苏州工业园区和顺路1号博济生能科技园210室
联系电话	0512-87186613 13912619019

产品详情

品牌	LAC	型号	带旋转罐的煅烧炉
最大电压	220 (V)	功率	xx (W)
额定温度	1200 ()	主要用途	该熔炉适用于实验室样品，如钛白产品等

calcining furnace with rotating retort kr	
煅烧炉kr	
application	应用范围：
the furnaces are suitable for calcinations of laboratory samples e.g. production of titanium white	该熔炉适用于实验室
description of furnace construction:	结构描述：
*frameless structure with jacket made of bent sheet	· 无框架结构的可弯
*two-section door made of tub-shaped bent sheet filled with mineral fibre plate, opening to sides	· 侧开双扇炉门由管
*chamber consisting of light-weighted bricks, into grooves of which heating spirals are located; another insulation layers consists of mineral fibre mat and silicate plate	· 炉箱由轻砖和纤维
*quartz retort fastened in a rotating and sliding mechanism which provides for automatic insert of the retort batch into the furnace	· 石英罐设在一个旋
*retort rotation controlled by plc	· 曲颈罐旋转由plc控
	· 电热偶

*batch thermocouple opening into the retort

*furnace fitted with own table

*switchboard on right side of the furnace

*cable with single-phase plug

*plc and industry controller enabling to save 30 control programs in memory, each program may include up to 15 steps; the operator may start the selected program on specified date and hour by means of real-time clock

*s-type thermocouple, contactless switch relay

standard design of the furnace includes:

*table

*retort mechanism

*exhaust fan (with injector) aerating the retort space

*2 thermocouples

*switchboard with electrical equipment and controlling elements

benefits:

*stainless steel jacket provides for long life of the furnace;

*attractive design;

*corrosive matters that may release from the batch are exhausted by injector fan, thus protecting heating spirals;

*perfect temperature distribution atdin17052-1

*premium insulation materials (low electricity consumption, possibility of quick rise to required temperature);

*programmable temperature control featuring high accuracy;

*semi-conductor relay (more fluent and noiseless operation, minimum interference of surrounding devices);

*perfect workshop design, technical equipment and operation safety

- 熔炉与其桌子相符
 - 配电盘在熔炉右侧
 - 单向插座电缆
 - plc与工业控制器的
员可以按照安装的实际
 - s型热电偶，非接触
- 标准设计包括：
- 桌子
 - 曲颈瓶机械装置
 - 带有喷射器的排气
 - 2个热电偶
 - 带有电器设备和控
- 优点：
- 不锈钢炉罩延长熔
 - 设计独特
 - 注射排气扇使得仪
 - 完美的温度分布 (c
 - 超值绝缘材料（耗
 - 高精确程控温度控
 - 半导体继电器（操
 - 完美的车间设计、

可选型号：

类型	最高温度	内积	外部尺寸	内部尺寸		
lac	° c	l	mm	mm		
kr 30/12	1200	3	1100x1600x2100*	310x310x310		