

PPS Z650低吸水PPS

产品名称	PPS Z650低吸水PPS
公司名称	东莞市晶宏塑胶原料有限公司
价格	.00/个
规格参数	品牌:日本油墨 型号:Z650 特性:抗撞击,良好的抗热震性
公司地址	东莞市樟木头镇百果洞百顺小区三巷5号一楼(注册地址)
联系电话	076989977070 18200646066

产品详情

PPS Z650低吸水PPS---PPS is resistance heat especially; molding of properties

mold, Therefore. crystallinity of degree by affected

injection in important particularly is temperature wall

above be should it, Basically. PPS.DIC of molding

.Tc1,temperature crystallization-post the is that C120

is C150 to 130 of temperature wall mold The

temperature deflection The. recommended generally

resistance heat of indicator the is) DTUL (load under

is DTUL of dependence temperature mold the and

.16.6.Fig in show

impact and flexural on temperature mold of effect The

.respectively 18.6 and 17.6. strengths

mold as reduced slightly is strength Flexural

polymer linked cross on increased is temperature

,hand other the On. 3600 FZ and 1140 FZ based

temperature mold as increases strength flexural

impact The. based polymer linear the for increasing

mold as compounds all for reduced is strength

.increased is tem

聚苯硫醚：特别是耐热性；性能的塑造

因此，模具。结晶度受温度的影响

注射中特别重要的是壁温

基本上应该是上面的。PPS.DIC公司成型工艺

.Tc1，结晶后温度为C120

是模具壁温的150到130摄氏度

温度偏差。一般推荐

指示器的电阻热为DTUL（负载下

取决于温度和模具

图16.6.图示

影响和弯曲对模具温度的影响

分别为18.6和17.6。强度

模具强度略有降低

聚合物的交联温度升高

，另一只手。基于3600 – FZ和1140 – FZ

随着温度的升高，模具的抗弯强度增加

影响。线性聚合物

模具为复合材料，强度降低

.增加了tem