

144芯免跳接光缆交接箱各种配置全国包邮

产品名称	144芯免跳接光缆交接箱各种配置全国包邮
公司名称	宁波品悦通信设备有限公司
价格	10.00/台
规格参数	品牌:品悦通信 材质:SMC，冷轧板，不锈钢 规格:齐全
公司地址	浙江省宁波市慈溪市龙山镇大海路150号
联系电话	0574-63618503 15336620995

产品详情

144芯免跳接光缆交接箱各种配置全国包邮
4芯免跳接光缆交接箱各种配置全国包邮
???

SMC|OCC??96??144??288??576??1152??1440?? Cross
Connecting Cabinet for Communication Optical Cable YD/T 988-1998 1 ??
??|FTTH??|??|???

144???

?? ??

One, overview

1. ?????

1 this product is used for connecting devices in optical access network of trunk optical cable and wiring cable node, can realize the optical fiber

??YD/T988-2007?

Weld. Storage and distribution scheduling and other functions. Products conform to the technical standard of YD/T988-2007.

2. ?? 1? ??????SMC??,?

The 2 features 1) box made of high strength SMC unsaturated polyester corrosion prevention special synthetic materials, has high heat insulation, energy

????????????????????.

Resist the upheaval of climate and poor working environment.

2? ??? 3? ??? 4? ??? 5? ???FC,SC??

2) the box body adopts a positioning lock, life long brand lock, safe and reliable. 3) interconnection can realize optical cable, cross connection and fiber disc storage. 4) have reliable optical cable fixing and grounding protection device. 5) using fused wiring integration module, suitable for FC, SC optical fiber adapter installed; and can be placed in the channelizer

?????

The light distribution.

6? ??? 3. ????? 1??????

6) fiber allocation and scheduling are all positive operation. The 3 technical indicators 1) conditions of use

????????20????60? ???????25????55? ???????95????40??? ??????70Kpa~106Kpa 2??????

Ambient temperature from-20 DEG to 60 C storage temperature: - 25 DEG C: 55 relative humidity is less than or equal to 95% (40 C) atmospheric pressure: 70Kpa~106Kpa 2) photoelectric properties

????????????????????????????????????0.2dB

Connector insertion loss (including insert, swap, repeat) is less than or equal to 0.2dB

??????FC/PC?45dB FC/UPC?50 dB FC/APC?60 dB ??????????1000??

4. ?????

The return loss is greater than or equal to 45dB: FC/PC FC/UPC = 50 dB FC/APC = 60 dB plug endurance life is more than 1000 times. 4 housing characteristics

1? ???????????GB4208/IP65

1) case sealing protection grade: GB4208/IP65

2) static load capacity: a box shell > 980N > 500N side surface door hinge is greater than or equal to 200N

3) insulation resistance: high pressure protection and frame insulation resistance greater than 1000M (500V/DC)

4) voltage endurance: high voltage protection and rack communicated with 3000V DC for 1 minutes without breakdown and no arc phenomenon.

??

??

0.5db

pc?40db, UPC?50dB, APC?60dB

1000?0.2dB

???

3G?FTTH

288? (???)

???

120°

???

???

???

???

30mm?

20??

???

???

???

??????????,??????????,????????????????????,??,????????????????????.

????????????,????????????????,????????????????,????????????????.