

厂价--供应垃圾焚烧厂用FMS高温滤袋

产品名称	厂价--供应垃圾焚烧厂用FMS高温滤袋
公司名称	上海文森过滤技术有限公司
价格	98.00/件
规格参数	材质:FMS 适用范围:吸尘器、油烟机、风机、过滤器 用途:空气过滤
公司地址	中国 上海市浦东新区 上海浦东金桥金海路2588号
联系电话	86 021 60871038/60871035 13816379955

产品详情

材质	FMS	适用范围	吸尘器、油烟机、风机、 过滤器
用途	空气过滤	类型	高效
适用对象	空气	品牌	everspring
规格	ES-FMS880N-FB	编织方式	平纹
过滤精度	10 (μ m)	过滤面积	1 (m2)
性能	耐酸、耐碱、耐高温、耐 低温		

产品编号	es-fms880n
product code	
产品名称	氟美斯针刺毡880克
product name	fms needle felt 880gsm
纤维fiber	玻纤短纤维、p84纤维、美塔 斯纤维
	fiberglass staple fiber,p84 fibre,nomex fiber
基布scrim	玻纤基布fibergalss scrim
克重weight (gsm)	880
厚度thickness (mm)	3.0
宽度width (m)	2.2
透风量air permeability (l/m2/s)	150 ~ 350
断裂强度	经向warp 2300

tensile strength(n/5 × 20cm)	纬向weft	2800
断裂伸长率	经向warp	8
	纬向weft	10
tensile elongation(%)		
工作温度	连续continue	260
	瞬间instant	280
temperature ()		
表面处理	ptfe浸渍，热定型	
finish treatment	ptfe impregnation,heat setting	
抗酸性anti-acid	good	
抗碱性anti-alkali	good	
耐磨性anti-abrasion	good	
水解稳定性hydrolysis stability	middle	

上述产品技术参数源于抽样实验均值，仅供参考。

above data are the averages obtained from a series of typical by our lab and just for reference only.