

## 20L-50L旋转蒸发器

产品名称	20L-50L旋转蒸发器
公司名称	上海鸿经生物仪器制造有限公司
价格	.00/个
规格参数	材质:玻璃 规格型号:20L-50L 生产厂家:上海鸿经生物仪器制造有限公司
公司地址	上海市宝山区共康路957弄186号 - 8
联系电话	021-56428746 13311760350

## 产品详情

材质	玻璃	规格型号	20L-50L
生产厂家	上海鸿经生物仪器制造有限公司		

### 基本参数parameters旋转蒸发器rotary evaporator 10l ~ 50l

型号model	r1002b	r2002b	r2002k
蒸发瓶(l) evaporating flask(l)	10l / f125	20l / f125	20l / f125
收集瓶(l) receiving flask(l)	5l	10l	10l+5l
冷凝面积(m <sup>2</sup> ) condenser surface(m <sup>2</sup> )	0.6	1.15	
转速(rpm) rotation speed(rpm)	3 ~ 110		
蒸发速度(h <sub>2</sub> o) evaporation speed(h <sub>2</sub> o)	>3l/h	>5l/h	
到达真空reachable vacuum rate	133pa(1.33mbar,1torr)		
浴锅功率(kw) bath power(kw)	3kw	5kw	
静态温控范围及其波动	室温 ~ 99 (200) ± 2		
static temp.control range & wave( )	room temperature ~ 99 (200) ± 2		
浴锅尺寸(cm), 容量, 材质	35 × 35,	45 × 27,	
bath size,capacity,material	22l,sus304	40l,sus304	
电源power	220v, 20a		
整机尺寸(cm) dimensions(cm)	95 × 50 × 180h	110 × 60 × 210h	115 × 70 × 200h
功能配置functional configurations			
型号model	r1002b	r2002b	r2002k
ptfe组合密封ptfe seal assembly			

下出料bottom discharge valve				
连续进料continuous charge				
真空表vacuum meter				
变频调速				
frequency conversion speed control				
真空截止阀throttle valve for vacuum			/	
防冲管bumping tube				
数字温控				
temp control with digital display				
浴锅升降lifting heating bath			电动 / 手动electric / manual	
温控系统controls the system warm			pt100	
静音设计low noise				
低温冷阱cold trap				
蒸汽加热steam heating				
安全防护safety features			过电流保护，无火花控制	
			over-current protection,no-spark eletron	

符号含义： / -无， - 已配， - 可选（此选配功能必须在工厂生产时组装，不能单独另配）

注：相关型号不符具体参数与标准机型有少量差异，需另行确认。

symbol instruction: / - none , - equipped , - optional ( only available when ordering of product,not for separate sale )

note:some specifications of relevant models may have differences from that of standard model.details available at request.