

# 中铝中州 纳米氢氧化铝 H-WF-100 铝粉 阻燃剂 油墨级氢氧化铝

产品名称	中铝中州 纳米氢氧化铝 H-WF-100 铝粉 阻燃剂 油墨级氢氧化铝
公司名称	淄博韩锦新材料科技有限公司
价格	2000.00/吨
规格参数	
公司地址	山东省淄博市高新区北营北路31号
联系电话	15269366707

## 产品详情

中铝中州 纳米氢氧化铝 H-WF-100 铝粉 阻燃剂 油墨级氢氧化铝

关键词：中国铝业，纳米氢氧化铝填料，H-WF-100，阻燃剂填料，油墨级氢氧化铝

Aluminum Hydroxide



CAS NO. 21645-51-2

General Properties 常规属性

Molecular weight分子量	78	Mohs hardness	3
		摩氏硬度	
Density g/cm <sup>3</sup>	2.4	Ratio of refraction	1.58
密度		折光率	

Physical and Chemical Properties

Item	H-WF	H-WF -15	H-WF -25	H-WF -35	H-WF
------	------	----------	----------	----------	------

Model		-10				
Chemical constituent	Al(OH) <sub>3</sub> [%]	99.7	99.7	99.7		
	Al <sub>2</sub> O <sub>3</sub> [%]	64.5	64.5	64.5		
化学成分	SiO <sub>2</sub> [%]	0.05	0.05	0.05		
	Fe <sub>2</sub> O <sub>3</sub> [%]	0.01	0.01	0.01		
	Na <sub>2</sub> O [%]	0.30	0.30	0.30		
	Loss on ignition 灼减	35.0	35.0	35.0		
	Attached water 水分	0.4				
	+325 mesh 325目筛上	0.5	10	30	50	
	oil absorption 吸油率	27	22	20	20	
	Mean particle diameter 粒度 (D50)	9-12	13-18	22-27	30-40	40-
Whiteness 白度 [R457]	97	96	95	95		
PH value PH值		10.0 ± 1.5				

Notes: In this specification, the mean particle size can also be produced according to customer's req  
备注：可根据客户要求调整产品粒度

Applications :

Plastics and board fireproofing 工程塑料防火板

Coating, adhesives and electronic sealing material 涂层，胶黏剂，电子灌封料

insulating compound, conveyer belt 绝缘材料 输送带

Artificial stone and BMC and SMC 人造石，状模塑料，片状模塑料

Packaging :

Compound paper or plastic packaging 纸塑合一袋或塑编袋

Net weight: 25kg/bag, or 40 kg/bag or jumbo bag 25公斤/包或40公斤/包或集装袋