

SAE AS5272 TYPE I干膜润滑剂SANDSTROM LC-300

产品名称	SAE AS5272 TYPE I干膜润滑剂SANDSTROM LC-300
公司名称	上海恩莱保贸易有限公司
价格	.00/个
规格参数	
公司地址	上海市松江区金高路2388号813室
联系电话	86-021-20228098 13391171050

产品详情

SANDSTROM LC-300

NOTICE

Sandstrom LC-300 is a lead free lacquer-like dry film lubricant coating containing molybdenum disulfide and corrosion-inhibiting pigments. This Heat Curing material prevents corrosion, galling, seizing and fretting. It is a low-friction coating that exhibits long wear life when operated at -320 ° F to +400 ° F under loads exceeding 100,000 psi.

LC-300 may be applied by brush, dip, dip spin or spray method. After it is heat cured, LC-300 is virtually unaffected by atmospheric and fretting corrosion, solvents, acids, oils and degreasers and is not re-softened at elevated temperatures.

Basic Product Guidance:

- Use LC-300 or #099 on metals that may be adversely affected by a 1 hour @ 400 ° F bake cycle.
- Use 9A on metals not affected by higher bake temperatures.
- Use #099 to meet low VOC requirements.

Please consult Sandstrom Technical Rep during product selection process for best results.

OUTSTANDING FEATURE