

在线式铝箔封口机

| | |
|------|--|
| 产品名称 | 在线式铝箔封口机 |
| 公司名称 | 常州迅捷自动化设备有限公司 |
| 价格 | 23500.00/套 |
| 规格参数 | 电源电压:AC220V 50HZ 封口功率:3000~6000w 产地:江苏常州 |
| 公司地址 | 常州市金坛区西城路103号 |
| 联系电话 | 13775141889 18112889868 |

产品详情

高速双冷（风冷+水冷）电磁感应铝箔封口 KTC-4000C

High speed double cold (air cooling + water) electromagnetic induction aluminum foil sealing KTC - 4000 c

适用范围：

Scope of application:

广泛适用于农化、医药、食品、日化等塑料瓶及玻璃瓶产品的铝箔封口

Widely applicable to the agrochemical, pharmaceutical, food, cosmetic, etc. Products of aluminum foil sealing plastic bottle and glass bottle

特点：

Features:

1、隧道式感应头，封口速度快，

1, tunnel type induction head, sealing speed,

2、 优质304不锈钢外壳，符合GMP要求

2, high quality 304 stainless steel shell, in line with the GMP requirements

3、 主机微电脑控制，液晶显示，数字化设定输出功率，控制更加可靠；主机预留联控接口（通过预留的联控接口，方便外部控制封口机封口的启动和停止），方便整条生产线总控

3、 The host microcomputer control, LCD, digital set output power, control more accurate and reliable; host reserves associated control interface (by reservation joint control interface to facilitate sealing machine sealing of external control to start and stop), the whole production line to facilitate total control

4、 感应头高度、输出功率可调，启动无需预热，操作简单

4, sensing head height, adjustable output power, start without preheating, the operation is simple

5、 超静音冷却系统，有效降低环境工作噪音，水流量10-18L/分钟

5, ultra-quiet cooling system, effectively reduce the environment noise, water flow 10 to 18 l/min

6、 同型号封口机的产品零部件均可互换通用，维护更加方便

6, the product of the same model sealing machine parts all interchangeable gm, maintenance more convenient

7、 控制单元经过三防工艺处理，使用寿命更加持久，有效降低使用成本

7, the control unit after three process, more durable service life, effectively reduce the cost

8、 水箱内置，外观整洁大方

8, built-in water tanks, neat and easy appearance

9、 具有缺水、过热、堵瓶保护，有效加强系统的稳定性，运行更加稳定可靠

9, with water, overheating, plugging bottles of protection, effectively enhance the stability of the system, a more stable and reliable running

10、 主机自带有无铝箔剔除功能

The function of eliminating 10, host their own presence of aluminum foil

配置：主机（内置水箱）一台、感应头一只、升降支架一套、报警灯一只

A configuration: host (built-in tank), induction head a, lift a stent, an alarm lamp

(电源稳压装置、气动剔除装置、堵瓶监测为选配件)

(the power voltage stabilizing device, pneumatic rejecting device, plugging bottles of monitoring for options)

技术参数：

Technical parameters:

1、封口范围： 10mm - 100mm 100mm的需要定制

1, sealing range: 10 mm - 100 mm or greater or equal to 100 mm need to customize

2、供电电源：AC220V \pm 10% 50/60Hz 18A

2, power supply: AC220V 18 a plus or minus 10% 50/60 hz

3、封口速度：0-350瓶/分钟（以封口密封为准）

3, sealing speed: 0-350 bottles/min (the sealing seal shall prevail)

4、感应长度：200mm

4, induction length: 200 mm

5、输出功率：4000W（数字设定）（特殊可定制6000W）

5, the output power: 4000 w (digital set) (6000 w) special customized

6、机身尺寸：550*550*1500mm 感应器：630*120*90mm

6, the fuselage size: 550 * 550 * 1500 mm sensors: 630 * 120 * 90 mm

7、升降高度：600mm

7, lift height: 600 mm

8、整机重量：净重75kg

8, the weight: net weight 75 kg

9、使用环境：室内使用 60 湿度 80%

9, using the environment: indoor use 60 80% humidity

10、可以选配电源稳压和气动剔除装置

10, can be equipped with power supply voltage regulator and pneumatic removing device