

Jh21-110T Fixed Press

| | |
|------|-------------------------------|
| 产品名称 | Jh21-110T Fixed Press |
| 公司名称 | 浙江双穗锻压机床有限公司 |
| 价格 | .00/个 |
| 规格参数 | 类型:高速冲床 品牌:双穗 动力类型:联合传动 |
| 公司地址 | 瑞安市塘下镇海安东阳路32号 |
| 联系电话 | 86 0577 65270158 13736358088 |

产品详情

| | | | |
|--------|------------|-------|-------------------------|
| 类型 | 高速冲床 | 品牌 | 双穗 |
| 动力类型 | 联合传动 | 型号 | JH21-110 |
| 主电机功率 | 11 (kw) | 公称压力 | 1100 (kn) |
| 喉口深度 | 350 (mm) | 滑块行程 | 160 (mm) |
| 控制形式 | 数控 | 模柄孔尺寸 | 60*80 (mm*mm) |
| 布局形式 | 立式 | 适用范围 | 通用 |
| 适用行业 | 通用 | 行程次数 | Fixed:60;Variable:35-70 |
| 作用对象材质 | 金属 | 产品类型 | 全新 |
| 是否库存 | 否 | | |

jh21-110t c-framefixed bolsterpresses

features: the body is welded with steel plate to gain good rigidity and stable precision. the crankshaft is placed vertically, so the structure is compact and the contour is beautiful. using the combined pneumatic friction clutch and brake, so the engagement is smooth,the action is agile and the noise is low. gear pair adopts the flooding system lubrication. the slide block is six-face rectangle with longer guide track whose face is bronze panel, meanwhile an import hydraulic overload protector can be installed in the slide block with imported air pump and ring seal.its action is agile and reliable. there set lifting balance cylinder at the slide block with imported ring seal. the air pipeline is controlled by safely duplex value. the presses can be equipped with air cushion, automatic feed shaft, photo-electric protector, and various automatic equipments. the die set is adjusted by motor over jh21-110 press. the kind of press conforms to the safety standard of press.