

## J23-40T Inclinable Press

产品名称	J23-40T Inclinable Press
公司名称	浙江双穗锻压机床有限公司
价格	.00/个
规格参数	类型:普通冲床 品牌:双穗 动力类型:机械传动
公司地址	瑞安市塘下镇海安东阳路32号
联系电话	86 0577 65270158 13736358088

## 产品详情

类型	普通冲床	品牌	双穗
动力类型	机械传动	型号	J23-40
主电机功率	4 ( kw )	公称压力	400 ( kn )
喉口深度	210 ( mm )	滑块行程	100 ( mm )
控制形式	自动和点动	模柄孔尺寸	50*70 ( mm*mm )
布局形式	立式	适用范围	通用
适用行业	通用	行程次数	54
作用对象材质	金属	产品类型	全新
是否库存	否		

j23-40t c-frame inclinable presses

main structure features:

the press is characterized by sound universal performance.its body can be inclined in a certain scope so that the punched finished products or wasting material can slide from die.

j23-40 adopt secondary drive,which is characterized by stable performance and lower noise.the internally inserted roating key clutch inside has single and continual poeration standard.

the inserted balancer for j23-40 can improve running smoothness and security.

the press series is characterized by beautiful outlook and convenient maintenance,ease of adjustment.it is widely used for punching, blanking, cutting, bending, forming, light stretching and so on.

### j23型压力机技术规格

技术参数speciflcations	单位unit	j23-6.3	j23-10	j23-16	j23-25	j23-40	j23-63	
滑块公称压力nominal capacity	kn	63	100	160	250	400	630	
滑块行程 slide stroke	mm	35	50	60	75	100	100	
行程次数slide strokes per minute	times/min	140	145	125	78	54	40	
封闭高度maximum die set height	mm	225	260	310	345	380	430	
封闭高度调节量	mm	30	35	45	55	75	100	
die height adjustment								
滑块中心至机身距离	mm	130	130	170	200	210	290	
throat depth								
立柱距离distance between uprights	mm	160	180	220	250	300	430	
工作台板尺寸	前后f b	mm	240	245	300	355	400	570
	左右l r	mm	390	395	480	560	630	870
bolster size								
滑块底面尺寸	前后f b	mm	140	150	180	200	205	360
	左右l r	mm	140	150	210	230	230	395
slide bottom size								
模柄孔尺寸	直径dia	mm	30	30	40	40	50	50
	深度depth	mm	55	55	60	60	70	70
stemhole size								
工作台板厚度bolster thickness	mm	45	50	50	55	60	80	
工作台离地面距离bolster surface height	mm	725	770	800	830	900	950	
外形尺寸	前后f b	mm	900	900	1100	1345	1550	1950
	左右l r	mm	650	670	850	950	1150	1500
overall dimensions	高	mm	1580	1750	1950	2100	2280	2850
地脚螺栓距离distance between foundation bolts	前后f b	mm	485	590	800	850	950	1300
	左右l r	mm	380	400	470	580	590	920
电动机功率 motor power	kw	1.1	1.5	2.2	2.2	4	7.5	
重量 weight(approximate)	kg	480	580	1100	1550	2450	5560	

( 可根据用户要求定制产品 ) 本样本内容如有变更 , 恕不另行通知

the contents are subject to change without prior notice