

## S107系列（传统型）钒催化剂

产品名称	S107系列（传统型）钒催化剂
公司名称	北京威顿技贸有限责任公司
价格	.00/个
规格参数	品牌:三阳 产品规格:S107系列（传统型） 执行标准:化工行业HG2086-2004标准
公司地址	北京市朝阳区五里桥一街1号院10号楼三层
联系电话	86 010 65618808-59 13910204894

## 产品详情

品牌	三阳	产品规格	S107系列（传统型）
执行标准	化工行业HG2086-2004标准	主要用途	二氧化硫氧化制硫酸催化剂

### 特性

s107系列(传统型)低温钒催化剂，经过广泛收集用户意见我们对其各组分以最佳配方组合，使其各种性能得到最佳发挥，通过各种原料，各种规模的硫酸装置应用，在低温下的活性好，抗粉化能力强，筛分周期长，得到了用户的充分肯定。

### 指标

		型号	s107-ch	s107-ah
外观形状	形状		梅花状	环状
	直径mm(外径/内径)		11.5/4.0	11.5/4.0
	长度mm		10~25	10~25
	颜色		黄色	绿色
化学组份	五氧化二钒，质量分数%			6.3
物理性能	堆密度kg/l			0.50~0.65
	颗粒机械抗压碎强度n/cm			40
	磨损率%			5
适用范围	适用于各种原料气制硫酸系统，主要用于装填在转化器的一段表面和四段、五段，。			
包装	纤维纸桶、铁桶包装。			
储存与运输	防潮、防雨、小心轻放、禁止翻滚。			

如需了解更多信息，欢迎电话垂询0856-5650708或18985346558陶经理

### s107 series (traditional) of vanadium catalyst

#### performance

the s107 series (traditional) catalyst, of which formulation has been modified upon the mass customer feedback, is well balanced and optimized in the attributes of its performance. those proven attributes, e.g. good activity at low temperature, good hardness and the long mean-time-to-screening, have been verified by the applications in various sulfuric acid facilities with different feed gas and different capacity level. now s107 series is highly regarded by our customers.

#### properties

	type	s107-ch	s107-ah
appearance	shape	5-ribbed ring	ring
	diameter (i/o) (mm)	11.5/4.0	11.5/4.0
	length (mm)	10 ~ 25	10 ~ 25
	color	yellow à	deep or
composition	vanadium pentoxide (weight %)		6.3
physical properties	bulk density (kg/l)		0.50 ~ 0.65
	particulate strength (n/cm)		40
	ball mill hardness (%)		5
application	sulfuric acid facilities for different feed gas.  to be loaded in pass 5, pass 4 and the top of pass 1 in the converter.  operating temperature ranging from 410 to 550		
packing	fibre drum or metal drum		
storage & transportation	keep dry, rain proof, handle with care, do not roll		