

# PET绿色耐高温胶带/绿色胶带/工业胶带

产品名称	PET绿色耐高温胶带/绿色胶带/工业胶带
公司名称	珠海佳合电子产品有限公司
价格	8.00/平方米
规格参数	型号:JH-34G6 基材:pet 厚度:0.06/0.08 ( mm )
公司地址	珠海市金湾区三灶镇南涌路3号8栋304房
联系电话	86 756 7765108-2088/7765008 13005788975

## 产品详情

型号	JH-34G6	基材	pet
厚度	0.06/0.08 ( mm )	宽度	500 ( mm )
颜色	绿色/蓝色/红色	适用范围	容易撕除，不易断裂，撕除后不残胶，耐高温、耐酸碱、耐腐蚀.用于镀金过程中保护印刷电路板.
品牌	佳合	短期耐温性	180 ( )
胶系	硅胶		

产品名称：	pet绿胶带	产品编码：	jh-34g6
product:	pet green tape	grade no.:	jh-34g6

产品结构 ( product structure )

	pet膜petfilm
	硅胶silicone adhesive

产品参数 ( product data )

项目 ( item )	单位 ( unit )	数值 ( value )	备注 ( remark )
总厚度 total thickness	mm	0.060 ± 0.005	gb7125-1999
初粘力 initial tack	no/ball#	9#	astm-d3759
粘着力 holding power	n/25mm	8 ± 0.5	gb/t72792-1998
抗拉强度 tensile strength	n/25mm	120	gb7953-1987
伸长率 elongation	%	55	gb7953-1987
耐电压 voltage resistance	kv	6.2	
绝缘电阻 insulation resistance	m	106	
绝缘等级 insulation rank		f	
耐温性 heat resistance	/30分钟	200	
颜色 color		蓝/黄/绿色 blue/yellow/green	visual test ( 目测值 )

特性/用途 ( features /usage )

<p>喷漆、烤漆专用绿胶，容易撕除，不易断裂，撕除后不残胶，耐高温、耐酸碱、耐腐蚀。</p> <p>for painting and baking varnish; easy tear not easy break, no adhesive residue, high temperature and acid-alkali resistance.</p> <p>用于镀金过程中保护印刷电路板。</p> <p>for protecting pcb in the process of gold plating.</p>
---

注意事项 ( note )

<p>1、使用时，要注意被粘贴物的表面没有油污、粉末、灰尘、或其它离型剂。</p> <p>when applying pressure sensitive adhesive film to any surface, be sure that the surface free from oil or other surface contaminants as powder, dust or release agent.</p> <p>2、本胶带使用在含有增塑剂的材质上时，粘性会受影响，使用时注意检测。</p> <p>adhesive performance should be carefully checked when used on substrates containing plasticizers.</p> <p>3、在存储低于24 的低温、干燥环境下，从装运日期起有效期为六个月。</p> <p>a term of validity is six months from date of shipment, when stored in a cool &amp; dry place below 24 .</p>
---

