

MultiTherm 660导热油

产品名称	MultiTherm 660导热油
公司名称	上海恩莱保贸易有限公司
价格	12000.00/桶
规格参数	MultiT:MultiTherm 6
公司地址	上海市松江区金高路2388号813室
联系电话	86-021-20228098 13391171050

产品详情

Heat Transfer Fluid MultiTherm 660 is a uniquely engineered high-temperature synthetic heat transfer fluid used in non-pressurized / low-pressure liquid phase heating and cooling systems up to 660°F / 349°C.

Purpose MultiTherm 660 heat transfer fluid is highly engineered to provide fluid stability and long life. In the Gas Processing it is used in dehydrators, NGL reboilers as well as process equipment, in the Chemical Process to heat & cool reactors as well in heat recovery systems. Biodiesel Production benefits by being able to run at higher temperature in the distillation process and in Plastic Processing to provide consistent heat to molds or dies as well as laminating lines. This is just to name a few.

MultiTherm 660 heat transfer fluid is designed with a maximum film temperature of 710°F / 377°C, autoignition point of 810°F / 432°C and a maximum operating bulk temperature of 660°F / 349°C to provide users with a safe, durable & economical heat transfer fluid over other conventional thermal fluids.

Closed Loop SystemsMultiTherm 660 is designed for use in liquid-phase heat transfer systems, which the circulating loop is “closed” to the atmosphere. To maximize the product’s superior thermal stability, it is recommended that the system have inert gas blanketing the expansion tank. This will guard against exposure to air and water which will minimize oxidative degradation and maximize fluid life.