

SC16-6铜管端子 GS国赛

产品名称	SC16-6铜管端子 GS国赛
公司名称	乐清市国赛科技发展有限公司
价格	1.00/PCS
规格参数	品牌:GS国赛 型号:SC16-6 应用范围:电缆
公司地址	乐清市北白象镇马路角村（浙江新江仪表有限公司内三楼）
联系电话	86 0577 61891155

产品详情

品牌	GS国赛	型号	SC16-6
应用范围	电缆	种类	端子(terminal)
接口类型	AC/DC	形状	圆形
制作工艺	冷压	特性	导电
接触件材质	紫铜	绝缘体材质	无
芯数	无	针数	无
线长	不限 (mm)		

产品均通过了环保认证，质量优异。

材质：紫铜管						
型号	螺栓口直径	尺寸				导线截面(mm ²)
		d	d	l1	l	
sc 1.5-5	5.3	1.9	3.35	6.5	18.0	1.5
sc 2.5-4	4.3	2.6	4.0	7.0	18.0	2.5
sc 2.5-5	5.3	2.6	4.0	7.0	20.0	2.5
sc 4-5	5.3	3.2	4.8	7.5	20.5	4
sc 4-6	6.4	3.2	4.8	7.5	22.0	4
sc 6-5	5.3	4.1	5.5	8.0	24.0	6
sc 6-6	6.4	4.1	5.5	8.0	24.0	6
sc 6-8	8.4	4.1	5.5	8.0	26.0	6
sc 10-6	6.4	5.2	7.0	9.0	24.0	10

sc 10-8	8.4	5.2	7.0	9.0	25.0	10
sc 16-6	6.4	5.8	7.8	11.0	27.5	16
sc 16-8	8.4	5.8	7.8	11.0	29.5	16
sc 25-6	6.5	7.5	9.5	13.5	34.0	25
sc 25-8	8.4	7.5	9.5	13.5	34.0	25
sc 25-10	10.5	7.5	9.5	13.5	34.0	25
sc 35-6	6.4	8.4	11.0	14.5	37.0	35
sc 35-8	8.4	8.4	11.0	14.5	37.0	35
sc 35-10	10.5	8.4	11.0	14.5	38.0	35
sc 50-8	8.4	9.6	12.5	17.0	42.5	50
sc 50-10	10.5	9.6	12.5	17.0	42.5	50
sc 50-12	12.5	9.6	12.5	17.0	44.0	50
sc 70-8	8.4	12.0	15.0	19.5	50.0	70
sc 70-10	10.5	12.0	15.0	19.5	50.0	70
sc 70-12	13.0	12.0	15.0	19.5	50.0	70
sc 95-8	8.4	13.4	17.0	23.5	57.0	95
sc 95-10	10.5	13.4	17.0	23.5	57.0	95
sc 95-12	13.0	13.4	17.0	23.5	57.0	95
sc 95-14	15.0	13.4	17.0	23.5	57.0	95
sc 120-10	10.5	15.5	19.5	26.0	63.0	120
sc 120-12	13.0	15.5	19.5	26.0	63.0	120
sc 120-14	15.0	15.5	19.5	26.0	63.0	120
sc 150-12	13.0	16.7	21.0	29.0	71.0	150
sc 150-14	15.0	16.7	21.0	29.0	71.0	150
sc 150-16	17.0	16.7	21.0	29.0	71.0	150
sc 185-12	13.0	18.7	23.7	33.0	79.0	185
sc 185-14	15.0	18.7	23.7	33.0	79.0	185
sc 185-16	17.0	18.7	23.7	33.0	79.0	185
sc 240-12	13.0	20.6	26.0	40.0	91.0	240
sc 240-14	15.0	20.6	26.0	40.0	91.0	240
sc 240-16	17.0	20.6	26.0	40.0	92.0	240
sc 240-18	19.0	20.6	26.0	40.0	92.0	240
sc 300-16	17.0	24.0	30.0	44.0	100.0	300
sc 300-20	21.0	24.0	30.0	44.0	102.0	300
sc 400-16	17.0	27.0	34.0	46.0	102.0	400
sc 400-20	21.0	27.0	34.0	46.0	113.0	400
sc 500-16	17.0	30.0	38.0	50.0	123.0	500
sc 500-20	21.0	30.0	38.0	50.0	123.0	500
sc 630-20	21.0	35.0	45.0	56.0	135.0	630
sc 800-bl	-	39.0	50.0	60.0	170.0	800
sc 1000-bl	-	44.0	56.0	87.0	200.0	1000