

固纬 GFC8270H 固纬 频率计 固纬 天津

产品名称	固纬 GFC8270H 固纬 频率计 固纬 天津
公司名称	青岛东方嘉仪电子科技有限公司
价格	10.00/个
规格参数	品牌:台湾固纬INSTEK 型号:GFC-8270H 测量范围:0.01Hz~1.3GHz (Hz)
公司地址	山东省青岛市李沧区万年泉路237号中海国际大厦2507
联系电话	13791934995

产品详情

品牌	台湾 固纬 INSTEK	型号	GFC-8270H
测量范围	0.01Hz ~ 1.3GHz (Hz)		

东方嘉仪注册了应用于仪器仪表销售领域的“东方嘉仪”商标，力争打造仪器仪表销售行业专业守信的电子商务环境。东方嘉仪销售各类进口及国产仪器仪表，良好的进货渠道、专业的销售队伍、快捷的反应速度，竭诚为广大客户服务。

东方嘉仪天津分公司电话：022-89569428 28233040 传真：022-28233040 手机：158-2254-5366

东方嘉仪公司为台湾固纬仪器授权代理商。提供选型指导，欢迎洽询。

显示	8 位数 with hz, khz, mhz, ghz, s, ms, μ s, ns and overflow
gate time	continuously vary from 10ms to 10s, or 1 period of input depending on whichever is greater
准确度	+ (解析度 + 时基误差)
频道 a	
范围	dc 耦合 0.01hz ~ 120mhz ; ac 耦合 30hz ~ 120mhz
感度	10mvrms typical ; 50mvrms max
耦合	ac 或 dc, switchable
滤波器	low pass, switchable in or out for channel a.-3db point of nominally 100khz
阻抗	1m //40pf

衰减器	x 20db
触发准位调整	-2.5 vdc to +2.5 vdc
解析度	the maximum resolution for frequency measurement is 100nhz for 1hz and 0.1hz for 100mhz input respectively, and for period measurement is 10ns for 1hz and 0.1fs (f=10-15) for 100mhz input respectively.at least 7,6,5 digits are display for 1s, 100ms, 10ms gate time respectively
period range	8ns to 100s at least 7 digits displayed for per second of gate time
频道 b	
范围	50mhz to 2.7ghz
感度	< 50mvrms (10mvrms typical)
耦合	ac only
时基	
aging rate	1 ppm, per month
温度	5 ppm 23 ° c + 5 ° c
电源变化	+ 0.005 ppm for + 10% 变化
使用电源	
	交流 100v/120v/220v/240v ± 10%, 50/60hz
附件	
	操作手册 × 1,电源线 × 1,测试线 × 2
尺寸及重量	
	230(宽) × 95(高) × 280(长) mm约 2.2 公斤