


台湾华乐士TPAK2-18

产品名称	台湾华乐士TPAK2-18
公司名称	上海颐索机电设备有限公司
价格	.00/个
规格参数	材质:铸铁 驱动方式:电动 泵轴位置:边立式
公司地址	上海市松江区叶榭镇叶新公路367号A幢113室
联系电话	021-34530583

产品详情

材质	铸铁	驱动方式	电动
泵轴位置	边立式	叶轮结构	敞开式叶轮
叶轮数目	单级	叶轮吸入方式	单吸式
性能	不阻塞	品牌	台湾华乐士
型号	TPAK2-18	流量	5 (m3/h)
扬程	7 (m)	排出口径	25 (mm)

homeall productstpak series	線上公司簡介影片觀賞													
tpak series														
頁 1 / 2	<p>model:tpak seriescoolant pumps</p>  <table border="1"> <thead> <tr> <th>domestic</th> <th>commercial</th> <th>industry</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>*</td> </tr> </tbody> </table> <p>* note:</p> <table border="1"> <thead> <tr> <th>50hz</th> <th>60hz</th> <th>50/60hz</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>*</td> </tr> </tbody> </table>		domestic	commercial	industry			*	50hz	60hz	50/60hz			*
domestic	commercial	industry												
		*												
50hz	60hz	50/60hz												
		*												

* note:

[see details ...](#) [download paper..](#)

performance curves:

application:the tpak series coolant pump is design for the circulation and spraying of cooling lubricants, especially for machine tools.this series may use on all machine tools performing turning, milling, drilling, cutting, slitting, grinding etc. operation.it is suitable to carry liquidssuch as water, coolant, light oil and other clean, non aggressive matters.

pump construction:the pump is one-chamber vertical centrifugal pump, co-axial pump/motor design, impellers mounted on

motor:nominal speed : 2900 / 3500 rpmfrequency range : 50 / 60 hzstandard voltages : single-phase (tpak 1)50hz: 100-132v
200-255vthree phases (tpak 1 ~ tpak 8)50hz: 200-255v / 380-440v60hz: 200-255v / 380-480venclosure class : ip54insulation
:max. flow : 230 l/minmax. head : 17mmax. ambient temperature : +40 ° cmax. liquid temperature range : +90 ° cmax. oper