

狮力昂Sliontec UV膜NO.6360-25

产品名称	狮力昂Sliontec UV膜NO.6360-25
公司名称	上海微赋斯电子科技有限公司
价格	.00/个
规格参数	狮力昂:Sliontec UV膜:NO.6360-25 日本:日本
公司地址	上海市闵行区七莘路50号10幢201室
联系电话	021-64929685 18016274100

产品详情

上海微赋斯电子科技有限公司是狮力昂UV膜6360系列中国区一级代理商，直接和日本原厂Maxell拿货，质量有保证，价格也非常有优势，型号和尺寸齐全，并且有大量现货，欢迎咨询订购。

UV Dicing Tape:No.6360-25

High adhesion

Feature:

Non-PVC backing is used

High-Pressure mercury lamp or black light can be used as light source

Isotropic performance at expanding process

Property:

Item No.	No.6360-25
Color	Translucent
Thickness (um)	Transparent
Liner:38um	150
Peel strength	10
[N/10mm] () :After UV	SUS 3.40(0.22)
	Glass 3.80(0.23)

	SI wafer	3.80(0.23)	
Holding Power	40 /24hour	< 0.1mm	
Tensile Strength (Before UV) (TD/MD) (N/10mm)		30/30	
Elongation (Before UV) (TD/MD) (%/10mm)		910/840	

UV irradiation condition : High-pressure mercury lamp, 75mW/cm² at 365nm, for 4 sec (300mJ/cm²)

Peel Strength (90 Peel) : Pass the 2kg roller in each direction at a rate of 300mm/min. Aging time ; 20min. Rate of peel ; 300mm/min.

Holding power : Pass the 2kg roller in each direction at a rate of 300mm/min. Load ; 1kg/25mm × 25mm

TD : Transverse Direction, MD : Machine Direction