

# 多利吉(劲永PQI)Hi-Speed Series级工业军工蓝标宽温128MCF卡

产品名称	多利吉(劲永PQI)Hi-Speed Series级工业军工蓝标宽温128MCF卡
公司名称	北京元大兴业科技有限公司
价格	80.00/个
规格参数	品牌:劲永PQI 类型:CF卡
公司地址	北京市海淀区上地三街9号A座702B室
联系电话	010-62985650 18001122965

## 产品详情

品牌	劲永PQI	型号	Hi-Speed Series – Industrial CF
类型	CF卡	容量	128MB
传输速率	40000 (KB/s)	加印LOGO	可以
是否提供加工定制	是		

## 产品细节

商品名称	industrial cf card
產品敘述	工業 cf 卡
图片	
商品特点	? 符合rohs 規範? compact flash 介面? 無噪音? 低耗電? 無延遲? 耐震? 支援pio mode
型號	ac86-xxxxr6gxx
介面	50pin smt connector (type i)
儲存容量	128mb~16gb
傳輸速率	dual mode:read:up to 40mb/sec, write:up to 30mb/sec
電源	voltage dc +3.3v ± 5% or dc +5.0v ± 10%
耗電量	active mode: 24.1ma/ 26.5ma (3.3v/ 5.0v)

產品尺寸	3.3 x 36.4 x 42.8 mm (0.13 x 1.43 x 1.69 in)
實際重量	12 g (0.03 lb)
操作環境	? 溫度 : 0 ~+70 ? 溼度 : 8%~95% 震動測試 : 15g? 衝擊測試 : 1000g?mtbf:2,000,000 hours?讀寫次數:5,000,000 times

型号 specification		gata series – industrial cf card solution	
容量	128mb to 16gb		
电压	dc +3.3v ± 5% or dc +5.0v ± 10%		
界面	50 pin cf (ata) interface		
flash 顆粒	nand type slc flash based		
标准	cf 3.0, ata/atapi-5 compatible		
传输模式	pio mode:0-6, multi word dma mode: 0-4, ultra dma mode: 0-4		
渠道模式	dual channel	single channel	
读取速度(est.)	40 mb/sec	20 mb/sec	
写入速度(est.)	20 mb/sec	10 mb/sec	
notice: the value is various bases on the testing platform.			
功耗	<95ma in operation		
工作温度	0 ° c to 70 ° c, (industrial type)-40 ° c to 85 ° c (wide temperature type)		
工作湿度	10% to 95%, (30 ° c max. wet bulb temp)		
平均无故障时间	2,000,000 hours		
耐久性	testing condition: 3sec/cycle – repeated plug/unplug 10,000 cycles		
震动	sine (non-op) : 15grms, 10 ~ 2000hz random vibration (op) :6grms, 10~500hz		
掉落	75 cm height		
数据保留	10 years without requiring power support		
ecc	4 symbols ecc per 512bytes		
wear leveling	static wear-leveling		
safety certification	ce, fcc		
hsf guaranty	rohs, reach svhc		
外观尺寸	36.4 x 42.8 x 3.3 mm		
重量	<12gram		

其他产品

元大简介

产品