## 以色列OPHIR测量显示一体工业用激光功率计Comet 10K

产品名称	以色列OPHIR测量显示一体工业用激光功率计C omet 10K
公司名称	深圳市嘉士达精密仪器有限公司
价格	16800.00/台
规格参数	品牌:以色列OPHIR 型号:Comet 10K 功率范围:200W -10kW
公司地址	西乡街道臣田社区宝民二路东方雅苑A100
联系电话	4006608810 18820263964

## 产品详情

COMET 10K?????

20W ? 10kW

??

COMET????????? 10 ?????

??????????

?? 10kW

?? 100 ?????

???

Comet 10K ???????????????? 100 ??? ????????? 20 ????????? 200W ? 10kW ???? ????????? 0.98 – 1.07m ? 10.6m ?????

型号 Comet 1K Comet 10K Comet 10K-HD

作用 For powers to 1kW For powers to 10kW For high power density beams

吸收类型 Broadband Broadband with reflective cone

探测范围u	0.2 - 20		beam spreader 0.98-1.07 and 10.6		0.98-1.07 and 10.6			
m 探测孔径m m	则孔径m 50mm		100mm		55mm			
功率模式 功率范围 重复性	20W to 1kV ± 1% for sa temperature	me initial	200W to 10kW ± 1% for same initial ten		200W to 10kW nperature			
平均值	Power	Damage Threshold	Damage Threshold					
功率密度 kW/cm2						Beam dia<4	10	Beam dia >40
	100W 200W 300W 500W 1kW	10 8 3kW 5kW 4	1kW 2kW 2.5 1.5	3.5 2.8 8 6 1	10 6	5 3	2	
5 功率准确度 ± 2% ± 1W from 20W +/-% to 1kW			5 $\pm$ 2% from 1kW to 10kW $\pm$ 2% from 1kW to 10kW					
功率线性度 +/-%		1kW 4kW	4kW	3kW	2	3	10kW	
之前的阅读 次数	ţ.							
探头必须是	<u>1</u>	0.3		0.3		1		
冷却(起始 温度为 25°C)	4							
能量密度	0.8 30		0.8		3			
J/cm2 <100ns 10s	50 Initial reading 10s after exposure,		150 Initial reading 20s after exposure,		Initial reading 30s after exposure,			
1ms 10ms 阅读时间 温度补偿	final reading 70s after exposure final reading 20s after final reading 40s after exposure exposure Temperature compensated to give accurate readings independent of starting probe temperature 70 ° C before measurement, 140 ° C after measurement 2x8 character LCD. Character height 5mm. CE Approved. AUTO: Automatic measurement with laser set to 10s timed exposure. Unit senses temperature rise and measures automatically.							
	NAANII IAL.	س عموما ما سوما	araba in franc	+ of booms for	معطالمال	na ta indiasts	040 W4 0 10 d = 4 = -	_

MANUAL: User places probe in front of beam for 10s. Unit beeps to indicate start and stop measurement points.

History: Stores last three readings. Calibration: Can be recalibrated by user.

电池 2 x AA. Lifetime in normal use

approximately 1 year.

1.2 1.2

重量 kg 认证 CE, China RoHS CE, China RoHS

版本 V2 V1

序号 7Z02705 7Z02706 7Z02702