

台湾希世比蓄电池12V100AH详细规格尺寸

| | |
|------|-------------------------------------|
| 产品名称 | 台湾希世比蓄电池12V100AH详细规格尺寸 |
| 公司名称 | 北京兴业荣达电源设备有限公司 |
| 价格 | 536.00/只 |
| 规格参数 | 品牌:台湾CSB希世比 型号:12V100AH 产地:台湾 |
| 公司地址 | 北京市昌平区回龙观西大街85号2层210 |
| 联系电话 | 17812191201 17812191201 |

产品详情

CSB蓄电池 GPL1000

GPL12100012 V100.0AhGPL 121000 is a general purpose battery up to 10 years expected life under normal float charge. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.

| | |
|------------|---|
| 局数 | 6 |
| 电压值 | 12 V |
| 安培数 | 100Ah @ 20hr-rate to 1.75 volts per cell @ 25 ° C (77 ° F) |
| 重量(kg) | Approx. 33.5kg. (73.85 lbs.) |
| 大放电电流5秒(A) | 800A (5 sec.) |
| 内阻(m) | 3.5m |
| 温度工作范围 | Discharge : -15 ~50 (5 ° F~122 ° F)Charge : -15 ~40 (5 ° F~104 ° F))Storage : -15 ~40 (5 ° F~104 ° F) |
| 一般使用温度工作范围 | 25 ° C ± 3 ° C (77 ° F ± 3 ° F) |
| 浮充使用充电条件 | 13.5 to 13.8 VDC/unit Average at 25 ° C (77 ° F) |
| 建议充电大电流 | 30A |

| | |
|----------|---|
| 均充使用充电条件 | 14.4 to 15.0 VDC/unit Average at 25 ° C (77 ° F) |
| 自放电 | It should be more than 75% of the capacity that before storage after stocked for 6 months at ambient temp. 25 |
| 端子 | I2-Thread lead alloy recessed terminal to accept M6/M8 bolt |
| 电槽组材质 | Polypropylene(UL 94-HB) & Flammability resistance of (UL 94-V0) can be available upon request. |