

# 16通道100GHz密集波分复用器 ( DWDM )

产品名称	16通道100GHz密集波分复用器 ( DWDM )
公司名称	中山市华思光电科技发展有限公司
价格	.00/个
规格参数	品牌:HUASMART 型号:HS0302163DW1-ZZ/ZZZ 通带波长范围:ITU+/-0.11 ( nm )
公司地址	中山市东区长江北路328号骏贤居E栋410室
联系电话	13923427960

## 产品详情

品牌	HUASMART	型号	HS0302163DW1-ZZ/ZZZ
通带波长范围	ITU+/-0.11 ( nm )	通带插入损耗	5.0 ( dB )
通带隔离度	25 ( dB )	反射波长范围	1500-1600 ( nm )
反射插入损耗	NA ( dB )	反射隔离度	NA ( dB )
波长热稳定性	0.001 ( nm/ )	方向性	45 ( dB )

dwdm module

feature	application
*low insertion loss	*metro dwdm network system
*high isolation	*optical sensor system
*high reliability	*long haul dwdm system

specifications

parameters	specification
operating wavelength	1500-1600
channel spacing	100(y=1)
center wavelength	itu grid
channel passband	c +/-0.11
passband ripple	0.5
insertion loss	16ch 5.0
dimension	150x100x20

isolation (adjacent channel)	25
isolation (non-adj channel)	45
polarization dependent loss	<0.2
polarization mode dispersion	<0.5
return loss	>45
directivity	>45
fiber	smf-28e with 900um loose tube, >0.9m length
operating temperature	0 to 70
storage temperature	-40 to 85

\*insertion loss doesn't include connector. il will add 0.3db with per pair connectors

order information:

hs0302163dw1-zz/zzz(xx:channel count; zz/zzz:connector type)