

2通道100GHz密集波分复用器 (DWDM)

产品名称	2通道100GHz密集波分复用器 (DWDM)
公司名称	中山市华思光电科技发展有限公司
价格	.00/个
规格参数	品牌:HUASMART 型号:HS0302023DW1-ZZ/ZZZ 通带波长范围:ITU+/-0.11 (nm)
公司地址	中山市东区长江北路328号骏贤居E栋410室
联系电话	13923427960

产品详情

品牌	HUASMART	型号	HS0302023DW1-ZZ/ZZZ
通带波长范围	ITU+/-0.11 (nm)	通带插入损耗	1.8 (dB)
通带隔离度	25 (dB)	反射波长范围	1500-1600 (nm)
反射插入损耗	NA (dB)	反射隔离度	NA (dB)
波长热稳定度	0.001 (nm/)	方向性	45 (dB)

dwdm module

feature	application
*low insertion loss	*metro dwdm network system
*high isolation	*optical sensor system
*high reliability	*long haul dwdm system

specifications

parameters	specification
operating wavelength	1500-1600
channel spacing	100(y=1)
center wavelength	itu grid
channel passband	c +/-0.11
passband ripple	0.5
insertion loss	2ch
	1.8

dimension	100x80x10	
isolation (adjacent channel)	25	
isolation (non-adj channel)	45	
polarization dependent loss	<0.2	
polarization mode dispersion	<0.5	
return loss	>45	
directivity	>45	
fiber	smf-28e with 900um loose tube, >0.9m length	
operating temperature	0 to 70	
storage temperature	-40 to 85	

*insertion loss doesn't include connector. it will add 0.3db with per pair connectors

order information:

hs0302023dw1-zz/zzz(xx:channel count; zz/zzz:connector type)