

四通道粗波分复用器 (4CH CWDM Module)

产品名称	四通道粗波分复用器 (4CH CWDM Module)
公司名称	中山市华思光电科技发展有限公司
价格	.00/个
规格参数	品牌:HUASMART 型号:HS0302043CW2 通带波长范围:中心波长+/-6.5 (nm)
公司地址	中山市东区长江北路328号骏贤居E栋410室
联系电话	13923427960

产品详情

品牌	HUASMART	型号	HS0302043CW2
通带波长范围	中心波长+/-6.5 (nm)	通带插入损耗	2.0 (dB)
通带隔离度	30 (dB)	反射波长范围	1260-1620 (nm)
反射插入损耗	NA (dB)	反射隔离度	NA (dB)
波长热稳定度	NA (nm/)	方向性	50 (dB)

feature	application
*low insertion loss	*enterprise network system
*high isolation	*optical sensor system
*high reliability	*access cwdm system

parameters	specification					unit
operating wavelength	1470-1610(y=1);1270-1610(y=2)					nm
channel spacing	20					nm
center wavelength	itu grid					nm
channel passband	c + 6.5					nm
passband ripple	0.5					nm
insertion loss	1ch	2ch	4ch	8ch	16ch	db
	0.7	1.5	2.0	3.0	5.0	
dimension	5.5(d)x34	100x80x10			120x80x18	mm
isolation (adjacent channel)	30					db
isolation (non-adj channel)	45					db
polarization dependent loss	<0.2					db
polarization mode dispersion	<0.5					ps

return loss	>50	db
directivity	>50	db
fiber	smf-28e with 900um loose tube, >0.9m length	
operating temperature	0 to 70	oc
storage temperature	-40 to 85	oc

*insertion loss doesn't include connector. it will add 0.3db with per pair connectors

order information:

hs0302xx3cwy-zz/zzz(xx:channel count; zz/zzz:connector type)