

M18连接器 接近开关 DINGCHEN

产品名称	M18连接器 接近开关 DINGCHEN
公司名称	上海定宸传感器有限公司
价格	.00/个
规格参数	品牌:DINGCHEN 型号:FN5-M18G12-NOD1 反应频率:800Hz
公司地址	上海市金山区金山卫镇钱鑫路279号130室
联系电话	13918563755

产品详情

品牌	DING CHEN	型号	FN5-M18G12-NOD1
反应频率	800Hz	额定电压	10-30 (V)
额定电流	200mA (A)	检测距离	5 (mm)
产品认证	CE		

特点

能检测各种金属 使用寿命长、高可靠性

内部元件全部采用进口件 短路、极性反接保护 防水等级：ip67，可在水中应用
m12连接器安装方便

		直流3线/dc 3-wire	
型号/type			
	nnp.no	fn5-m18g12-nod1	mn8-m18g12-nod1
	nnp.nc	fn5-m18g12-ncd1	mn8-m18g12-ncd1
	nnp.no+nc	fn5-m18g12-nhd1	mn8-m18g12-nhd1
	ppp.no	fn5-m18g12-pod1	mn8-m18g12-pod1
	ppp.nc	fn5-m18g12-pcd1	mn8-m18g12-pcd1
	ppp.no+nc	fn5-m18g12-phd1	mn8-m18g12-phd1
外形规格/form factor		m18*50	m18*60
安装方式/installation		齐平/shielded	非齐平/unshielded
检测距离/sensing distance		5mm	8mm
建议距离/recommended distance		0...4mm	0...6.4mm
开关频率/switching frequency		1000hz	800hz
重复精度/repeatability		5%	
迟滞/hysteresis		± 10%	
保护电路/protection circuit		短路、极性反接保护	

电压降/voltage drop	1.5v dc
电源电压/supply voltage	10-30v dc
负载电流/output current	200ma
空载电流/no-load supply current	10ma
输出显示/output display	黄色指示灯/yellow led
工作温度范围/operating temperature	-25...70
环境湿度/humidity	35-95%rh
外壳材料/housing material	镀镍黄铜/nickel plated brass
连接方式/connection	m12连接器/m12 connector

直流2线/dc 2-wire

型号/type	no	fn5-m18g12-dod1	mn8-m18g12-dod1
	nc	fn5-m18g12-dcd1	mn8-m18g12-dcd1
外形规格/form factor		m18*50	m18*60
安装方式/installation		齐平/shielded	非齐平/unshielded
检测距离/sensing distance		5mm	8mm
建议距离/recommended distance		0...4mm	0...6.4mm
开关频率/switching frequency		800hz	500hz
重复精度/repeatability		5%	
迟滞/hysteresis		± 10%	
保护电路/protection circuit		短路、极性反接保护	
电压降/voltage drop		6v dc	
电源电压/supply voltage		10-30v dc	
负载电流/output current		100ma	
空载电流/no-load supply current		10ma	
输出显示/output display		黄色指示灯/yellow led	
工作温度范围/operating temperature		-25...70	
环境湿度/humidity		35-95%rh	
外壳材料/housing material		镀镍黄铜/nickel plated brass	
连接方式/connection		m12连接器/m12 connector	

交流2线/ac 2-wire

型号/type	scr.no	fn5-m18g12-aoa1	mn8-m18g12-aoa1
	scr.nc	fn5-m18g12-aca1	mn8-m18g12-aca1
外形规格/form factor		m18*60	m18*60
安装方式/installation		齐平/shielded	非齐平/unshielded
检测距离/sensing distance		5mm	8mm
建议距离/recommended distance		0...4mm	0...6.4mm
开关频率/switching frequency		25hz	25hz
重复精度/repeatability		5%	
迟滞/hysteresis		± 10%	
保护电路/protection circuit		涌浪保护	
电压降/voltage drop		8v ac	
电源电压/supply voltage		25-250v ac	
负载电流/output current		400ma	
空载电流/no-load supply current		3ma	
输出显示/output display		黄色指示灯/yellow led	

工作温度范围/operating temperature	-25...70
环境湿度/humidity	35-95%rh
外壳材料/housing material	镀镍黄铜/nickel plated brass
连接方式/connection	m12连接器/m12 connector