

龙卷风深层清洗枪

产品名称	龙卷风深层清洗枪
公司名称	台州市中野机械有限公司
价格	180.00/套
规格参数	类型:龙卷风清洗枪TC-101B 型号:TC-101B 喷嘴口径:1.4/1.7/2.0
公司地址	中国 浙江 台州市 黄岩区东浦路212号
联系电话	86 0576 84689977/84285959 15958691100

产品详情

类型	龙卷风清洗枪TC-101B	型号	TC-101B
喷嘴口径	1.4/1.7/2.0	材质	铝 铜配件
适用范围	底漆和面漆	喷涂距离	2 (mm)
涂料供给方法	吸上式	涂料喷出量	4 (ml/s)
产品别名	龙卷风清洗枪	用途	清洗汽车及发动机、
混合方式	内混式喷枪	特殊喷枪	环保型喷枪

model	description	nozzle size	cup size	fluid delivery	air pressure	air inlet
h970p	hvlp	1.2/1.5/1.8	600ml	240ml/min	3.0kg/cm ²	1/4

源于专业技术的—制造工艺卓越的涂料传递效果—高效省漆人体工程学设计—操控灵活喷涂目标—轻松实现完美效果
 from professional technology--manufacturing processexcellent passing result of the material--efficient, paint savingergonomics design--flexible controllingspraying aim--realizing easily,perfect result

喷枪选定的标准standard of the choosing of spray gun

喷漆工件的大小？小型、大型喷枪的选定小零件、玩具、小件物品、汽车修补等 小形 (lph-50/100w-101) 大零件、车辆、建筑物，生产线喷漆，大件喷漆等 大形
 size of the item?choosing of s:mall,large spray gunsmall parts,toys,small thins,vehicle repairing,etc.....(small(lph-50/100/w-101)large parts,vehicles,buildings,production line paint spraying,large items

paint spraying...large喷涂量或者面积？涂料供给方式的选定（重力式·吸上式@压送式）少量喷涂，换色频繁的情况下，使用重力式(g型) 涂料杯方便少量及中量喷涂、换色喷涂多的情况下，使用吸上式(s)型容器罐方便。同色大量生产线喷涂等，用压送式(p型) 涂料泵和加压容器罐方便。 quantity or area?choosing of the method of the spraying metrial(gravity,suction,pressure)under the condition of small quantity of paint,and changing color frequently,the gravity(g) will be used.under the conditon of small and medium quantity of paint,suction(s) will be used.under the condition of using large quantity of paint in the largeproduction linr,pressure(p) will be used.

喷涂的步骤和粘度？涂料喷嘴口径和空枪帽的选定面漆（成品）喷涂等，要求特别微粒化的涂料粒子，根据涂料喷出量必须选择空气量多的型号，特别是金属性喷涂等，空气量必须尽可能大。涂料粘度和涂料喷嘴口径的选定必须根据涂料粘度选定喷嘴口径，一般来说，涂料粘度低选择小口径，涂料粘度高选择大口径。压送式型号，喷嘴口径小也能在低粘度到高粘度比较广的范围内使用。

procedure and viscosity of the spraying:choosing of the nozzle gun cap of the spray gun:when spraying the surface of the items,special particle is required,according to the paint spraying quantity,the type of large air volume will be chosen,esp.the metal spraying.the nozzle must be chosen according to the viscosity.generally speaking,if the viscosity is low,the small nozzle will be chosen,otherwise the big one.the pressure type,the small nozzle can be used in a large field,from low to high viscosity.

中野喷漆枪分类kinds of spray gun of johgyia重力式（上壶）虹吸式（下壶）压送式（压力桶） gravity (top pot) siphon (under pot) pressure(pressure barrel)中野公司所有手动喷枪的压缩空气接口国内均为快速气接头，all the air connector in johgyia are quick connector.中野公司中小型手动喷枪的涂料接口均为1/4英寸（外螺纹） manual control spray gun: the size of the connector is 1/4 inch(male) 大型手动喷枪为3/8英寸（外螺纹） large manual contro spar gun:3/8 inch(male)也可根据客户要求样式配置。 the connector can also ne deployed according to the guests.

怎样选用中野喷枪how to choose johgyia spray gun?底漆喷涂 面漆喷涂 小修补喷涂primer paint surface paint repair paint小幅面底漆喷枪 传统高压喷涂 高流量低气压喷涂 低流量中气压喷涂 环保省漆小修补喷枪small format primer spray gun,troditional high pressure spray gun,high flow low pressure spray gun,low flow medium pressure spray gun, environmental repairing spray gun.大幅面高效底漆喷枪 传统面漆喷枪 环保省漆面漆喷枪 hvlp省漆高效面漆喷枪large format efficient primer spray gun,troditional surface paint spray gun,environmental surface paint spray gun,hvlp efficient surface paint spray gun

一、喷涂距离1.distance of spraying:传统高压喷枪：18~23cm hvlp高流量低压喷枪：13~17cmtroditional high pressure spray gun:18--23cmhvlp high flow low pressuer spray fun:13--17cm二、喷枪移动方式 moving method

2.轨道式喷涂：喷枪与待喷件保持一定垂直距离，匀速往复运行。 track style spraying:keep the gun the item verticle,move forward and backward三、喷枪与涂装表面角度the angle of the gun and surface角度：喷涂时喷枪头部与被喷件永远保持垂直。 angle:when spraying, the head of the gun and the painted iten will keep verticle

