

铠装热电偶 武翔

产品名称	铠装热电偶 武翔
公司名称	常州市武翔仪表有限公司
价格	80.00/台
规格参数	品牌:武翔 型号:WRNK-191 分度号:K
公司地址	武进区横林镇崔桥街
联系电话	0519-88501215 13606116123

产品详情

品牌	武翔	型号	WRNK-191
分度号	K	测量范围	0-800 ()
允差等级	1	热响应时间	8 (s)

应用application

通常和显示仪表、记录仪表、电子计算机等配套使用。直接测量各种生产过程中的0 ~1300 范围内液体、蒸汽和气体介质以及固体表面温度。

it is usually connected with display meter, recording meter and computer, etc. to directly measure temperature of liquid, vapor, gas and solid surface ranging from 0 to 1300 during various production process.

特点features

- 1、热响应时间少，减小动态误差；
- 2、可弯曲安装使用；
- 3、测量范围大；
- 4、机械强度高，耐压性能好。

1.with quick response, reducing dynamic error;

2.optional installation methods;

3.wide measuring range;

4.high mechanical strength. good pressure-resistant performance.

工作原理operation theory

铠装热电偶的电极由两根不同导体材质组成。当测量端与参比端存在温差时，就会产生热电势，工作仪表便显示出热电势所对应的温度值。

the electrodes of armored thermocouple are made of two different materials.the temperature difference between measuring edn and reference edn results in pyroelectric potential,then the meter indicates the corresponding temperature to the pyroelectric potential.

型号	分度号		
		允差值	测温范围
wrn	k	± 1.5	-40~+375
		± 0.004 t	375~1000
wrm	n	± 1.5	-40~+375
		± 0.004 t	375~1000
wre	e	± 1.5	-40~+375
		± 0.004 t	375~800
wrf	j	± 1.5	-40~+375
		± 0.004 t	375~750
wrc	t	± 1.5	-40~+125
		± 0.004 t	125~350

敬请访问公司网站www.czwuxiang.com