

EUTECH 电导PH仪 PC300

| | |
|------|--|
| 产品名称 | EUTECH 电导PH仪 PC300 |
| 公司名称 | 上海双健仪器有限公司 |
| 价格 | .00/个 |
| 规格参数 | 品牌:EUTECH/OAKTON 型号:PC300 测量范围:见技术参数 |
| 公司地址 | 浦东新区航头镇沪南公路5842号 |
| 联系电话 | 021-64845672 13918465109 |

产品详情

| | | | |
|------|------------------|------|----------|
| 品牌 | EUTECH/OAKTON | 型号 | PC300 |
| 测量范围 | 见技术参数 | 测量精度 | 0.01 |
| 分辨率 | 0.1 | 电源 | 6V |
| 尺寸 | 190*20*45 (mm) | 用途 | 测量PH和电导率 |

| | |
|-----------------------|---|
| ph range | -2.00 to 16.00 ph |
| resolution / accuracy | 0.01 ph / ± 0.01 ph |
| calibration | up to 5 points with auto buffer recognition |
| ph bufferoption | usa: (ph 1.68, 4.01,7.00, 10.01, 12.45);nist: (ph 1.68, 4.01,6.86, 9.18, 12.45) |
| mv range | -600 to +600 mv |
| resolution / accuracy | 0.1 mv / ± 0.2 mv (-199.9 to +199.9 mv);1 mv / ± 2 mv (beyond ± 199.9 mv) |
| conductivity range | .. to 19.99, 199.9, 1999 μ s/cm; 0 to 19.99, 199.9 ms/cm |
| resolution / accuracy | 0.01, 0.1, 1 μ s/cm; 0.01, 0.1 ms/cm / $\pm 1\%$ full scale + 1 lsd |
| calibration | up to 5 points (1 point per range) |
| tds range | .. to 9.99, 99.9, 999 ppm; 0 to 9.99, 99.9 ppt |
| resolution / accuracy | 0.01, 0.1,1 ppm; 0.01, 0.1 ppt / $\pm 1\%$ full scale + 1 lsd |

| | |
|--------------------------------|---|
| calibration | up to 5 points (1 point per range) |
| temperature range | -10.0 to 110.0 ° c (14.0 to 230.0 ° f) (meter) |
| resolution / accuracy | 0.1 ° c (0.1 ° f) / ± 0.5 ° c (± 0.9 ° f) |
| calibration | offset in 0.1 ° c increments |
| cell constant (k) | 1.0 |
| temp. compensation | automatic / manual (0 to 100 ° c) |
| conductivity temp. coefficient | 0.0 to 10.0% per ° c |
| normalizationtemp. | 15.0 to 30.0 ° c (adjustable) |
| specialfunctions | auto-ranging;stability indicator; hold;ph slope/offset display & self-diagnostic |
| powerrequirements | 9v ac/dc adapter |