

中效静电袋式过滤器 加压过滤

产品名称	中效静电袋式过滤器 加压过滤
公司名称	上海展韵工贸有限公司
价格	.00/个
规格参数	原理:加压过滤 用途:空气过滤 样式:袋式
公司地址	上海市松江区九亭镇九新公路76号1604室
联系电话	86 021 57631897/57632871

产品详情

原理	加压过滤	用途	空气过滤
样式	袋式	性能	高效过滤、其他
适用对象	过滤器	适用对象性质	低温物料、其他
品牌	SZ	型号	pd1125
有效过滤面积	- (m ²)	主体材质	特殊滤材
适用范围	化工、石油、制药、汽车、轻工	产品类型	全新
DN	F1	外形尺寸	592*592*360*6B (mm)
设备重量	0.9 (Kg)		

容尘量高

透气性好

过滤效率高

使用寿命长

1) 用途：空气过滤系统预过滤，无尘室（clean room）之二级过滤，医院、药厂、电子厂、喷漆房等较高洁净空气要求等级的过滤系统，一般的大楼空气过滤设备，高效过滤器前级过滤。

2) 类型：袋式过滤器

3) 框架：铝合金、不锈钢或镀锌铁皮

4) 滤料：合成纤维

5) en799级别：35%、45%、65%、85%、95%

6) 耐温：100

7) 湿度：100%

8) 特性：8-1以镀锌铁或铝合金为结构外框。每个滤袋间一金属条固定，增加强度并防止滤袋于高风速时因分切之摩擦力而破裂。

8-2每个滤袋均有六道隔片平均分布于袋宽中，防止滤袋承受风压时过度膨胀、相互遮蔽，降低有效过滤面积与效率。

8-3每个滤袋边均超声波反思熔合，具有良好之气密性及结合强度，不产生漏气或开裂。

8-4采用超细合成纤维—特殊织法制成，避免旧式玻璃纤维材料所可能对人体造成的不适，滤材内含静电纤维，对次微米粉尘过滤效果特别良好，高捕尘率、高透气性、高使用寿命。

8-5有35%、45%、65%、85%、95%五种效率的袋型滤网可供选择

large dust holding capacity

high efficiency

breathable

long working life

application: it is applied to some equipments and systems like oven which the clean air is required

medium efficiency anti-static pocket filter

type: pocket filter

frame: aluminum alloy or stainless steel

media: synthetic fiber

en779 class : f5,f6,f7,f8,f9

temp. resistance :100

humidity: 100%

speciality:

ü galvanized iron or aluminum alloy frame

ü between each pocket has a metal stick to make frame more firm, and the separation material of each pocket can avoid the filter over expanded under the pressure.

ü ultrasonic sealing make the filter more strong and not easy to broke

ü adopt fine synthetic fiber instead of some fiberglass material

ü material has antistatic fiber, large dust holding capacity and long working life.

ü pocket mesh efficiency has five different type for choice: 35%, 45%, 65%, 85%, and 95%