

# VS系列电压传感器

产品名称	VS系列电压传感器
公司名称	湖南银河电气有限公司
价格	.00/个
规格参数	精度:0.05 量程:10000V以下
公司地址	长沙经济技术开发区漓湘路98号
联系电话	0731-88392988 17810377158

## 产品详情

电流输出型——隔离型电压传感器选型表产品型号额定电压(Vrms)测量范围 (Vp) 变比 (V/mA) 副边满量程输出 (mA) 测试精度(%FS)带宽 (kHz) 工频角差 (°) 工作电源资料下载VSA301-G150T01-I300500500:1001000.052000.0315 ± 15VDCVSA301-G150T02-I300500500:1001000.12000.0315 ± 15VDCVSA301-G150T03-I300500500:1001000.22000.0315 ± 15VDCVSA701-G150T01-I70010001000:1001000.052000.0315 ± 15VDCVSA701-G150T02-I70010001000:1001000.12000.0315 ± 15VDCVSA701-G150T03-I70010001000:1001000.22000.0315 ± 15VDCVSA152-G150T01-I150020002000:1001000.052000.0315 ± 15VDCVSA152-G150T02-I150020002000:1001000.12000.0315 ± 15VDCVSA152-G150T03-I150020002000:1001000.22000.0315 ± 15VDCVSA332-G150T02-I330060006000:1001000.1600.1AC220VVSA332-G150T03-I330060006000:1001000.2600.1AC220VVSA662-G150T02-I66001200012000:1001000.1300.2AC220VVSA662-G150T03-I66001200012000:1001000.2300.2AC220VVSA103-G150T02-I100002000020000:1001000.1100.6AC220VVSA103-G150T03-I100002000020000:1001000.2100.6AC220V

电流输出型——非隔离型电压传感器选型表产品型号额定电压(Vrms)测量范围 (Vp) 变比 (V/mA) 副边满量程输出 (mA) 测试精度(%FS)带宽 (kHz) 工频角差 (°) 工作电源资料下载VSA332-G150T01-N33006k6000:1001000.05600.1AC220VVSA332-G150T02-N33006k6000:1001000.1600.1AC220VVSA332-G150T03-N33006k6000:1001000.2600.1AC220VVSA662-G150T01-N660012k12000:1001000.05300.2AC220VVSA662-G150T02-N660012k12000:1001000.1300.2AC220VVSA662-G150T03-N660012k12000:1001000.2300.2AC220VVSA103-G150T01-N1000020k20000:1001000.05100.6AC220VVSA103-G150T02-N1000020k20000:1001000.1100.6AC220VVSA103-G150T03-N1000020k20000:1001000.2100.6AC220V

电压输出型——隔离型电压传感器选型表产品型号额定电压(Vrms)测量范围 (Vp) 变比 (V/mA) 副边满量程输出 (V) 测试精度(%FS)带宽 (kHz) 工频角差 (°) 工作电源资料下载VSV301-G150T01-I300500500:10 ± 100.05%2000.0315 ± 15VDCVSV301-G150T02-I300500500:10 ± 100.12000.0315 ± 15VDCVSV301-G150T03-I300500500:10 ± 100.22000.0315 ± 15VDCVSV701-G150T01-I70010001000:10 ± 100.052000.0315 ± 15VDCVSV701-G150T02-I70010001000:10 ± 100.12000.0315 ± 15VDCVSV701-G150T03-I70010001000:10 ± 100.22000.0315 ± 15VDCVSV152-G150T01-I150020002000:10 ± 100.052000.0315 ± 15VDCVSV152-G150T02-I150020002000:10 ± 100.12000.0315 ± 15VDCVSV152-G150T03-I150020002000:10 ± 100.22000.0315 ± 15VDCVSV332-G150T02-I330060006000:10 ± 100.1600.1AC220VSV332-G150T03-I330060006000:10 ± 100.2600.1AC220VSV662-G150T02-I66001200012000:10 ± 100.1300.2AC220VSV662-G150T03-I66001200012000:10 ± 100.2300.2AC220VSV103-G150T02-I100002000020000:10 ± 100.1100.6AC220VSV103-G150T03-I100002000020000:10 ± 100.2100.6AC220V

电压输出型——非隔离型电压传感器选型表产品型号额定电压(Vrms)测量范围 (Vp) 变比 (V/mA) 副边满量程输出 (mA) 测试精度(%FS)带宽 (kHz) 工

频角差 ( ° ) 工作电源资料下载VSV332-G150T01-N33006k6000:10 ± 100.05600.1AC220VSV332-G150T02-N33006k6000:10 ± 100.1600.1AC220VSV332-G150T03-N33006k6000:10 ± 100.2600.1AC220VSV662-G150T01-N660012k12000:10 ± 100.05300.2AC220VSV662-G150T02-N660012k12000:10 ± 100.1300.2AC220VSV662-G150T03-N660012k12000:10 ± 100.2300.2AC220VSV103-G150T01-N1000020k20000:10 ± 100.05100.6AC220VSV103-G150T02-N1000020k20000:10 ± 100.1100.6AC220VSV103-G150T03-N1000020k20000:10 ± 100.2100.6AC220V