

高效单晶A级片太阳能板(各种规格均有)

产品名称	高效单晶A级片太阳能板(各种规格均有)
公司名称	浙江天恩太阳能科技有限公司
价格	15.00/瓦
规格参数	品牌:天恩 型号:TE901 化学类型:单晶硅太阳电池
公司地址	浙江省绍兴市中兴南路851号
联系电话	86-0575-88376703

产品详情

品牌	天恩	型号	TE901
化学类型	单晶硅太阳电池	输出功率	- (W)
工作电压	12-220 (V)	转化效率	- (%)
填充因子	- (%)	工作电流	6.86 (A)
并联电阻	- (欧姆)	串联电阻	- (欧姆)
开路电压	- (V)	短路电流	- (A)
外形尺寸	1482 × 676 × 35	参考重量	7.3 (kg)
产品认证	CE	用途	太阳能发电

单晶太阳能电池组件参数	型号	尺寸	开路电压	短路电流	工作电压	工作电流	峰值功率	重量
		mm × mm	voc	isc	vmpp	impp	pmax	kg
	tep667201	1956 × 992 × 50	44.568	8.12	37.08	7.56	280	27kg
	tep 667201	1956 × 992 × 50	43.704	7.88	36.36	7.16	260	27kg
	tep 667201	1956 × 992 × 50	43.488	7.76	36.072	6.94	250	27kg
	tep667201	1956 × 992 × 50	42.984	7.64	35.568	6.76	240	27kg
	tep 667201	1956 × 992 × 50	41.976	7.48	34.92	6.6	230	27kg
	tep 665401	1482 × 992 × 50	32.94	8.12	27.81	7.56	210	22 kg
	tep 665401	1482 × 992 × 50	32.83	7.95	27.37	7.31	200	22kg
	tep 665401	1482 × 992 × 50	32.5	7.76	27.18	6.99	190	22kg

	× 50						
tep 643601	1482 × 676	21.528	7.61	16.48	6.86	120	7.3kg
	× 35						

产品外形及安装尺寸:

性能结构参数:

conditions(stc) 条件
irradiance (光照强度): 1000 w/m ²
cell temperature (测试温度): 25
am:1.5
system design characteristics (系统设计特点)
maximum system voltage 1000 v (最大系统电压1000v)
cells per module 72 (组件所需电池片数量72)
solar cells polycrystal silicon (多晶硅电池片)
cell dimensions 156 x 156 mm (电池片的尺寸)
operation temperature range:-40 ~85
thermal characteristics (温度系数)
noct 46
tk isc +0.08 %/
tk voc -0.35 %/
tk pm -0.36%/
rated power and maximum tolerance(最大允许额定功率)
module efficiency >13.3% (件转换效率)
rated power 230w~280w正负3%
warrantise (保证)
25-year limited warranty on power output warranties (25年的功率输出维护)
2-year limited warranty on materials and workmanship (两年的原料以及人力维护)