

# 白玉牌耐高温硅酸钙制品 硅酸钙

产品名称	白玉牌耐高温硅酸钙制品 硅酸钙
公司名称	宝鸡厚生科工贸发展有限公司
价格	8.00/个
规格参数	材质:硅酸钙 产地:陕西宝鸡 产品类别:窑炉工业窑炉用保温材料
公司地址	宝鸡市渭滨区经二路东段北6号
联系电话	0917-3372253 13991709037

## 产品详情

材质	硅酸钙	产地	陕西宝鸡
产品类别	窑炉工业窑炉用保温材料	产品种类	保温板
导热系数（常温）	0.0.056	等级	优质
规格	300*600-20-200	抗弯强度	0.45
抗压强度	0.835	品牌	白玉牌
使用温度	1050	形态	其他
形状	片状	应用范围	保温层

我公司是生产硅酸钙绝热制品的专业生产厂家，生产采用国际最先进的动态水热合成工艺及日本专用压机设备，主要生产ii型硅酸钙绝热制品（gb/t10699-1998）。其主晶相为硬硅钙石，由硅质原料和钙质原料经过动态水热合成。在反应过程中，硬硅钙石形成纤维状或针状的晶体，这些晶体互相缠绕成中空的硬硅钙石二次粒子，直径一般在十几至几十微米。当料浆经过水热合成后，加入添加剂和增强材料，然后压滤成型，在压滤过程中，硬硅钙石二次粒子形成最紧密堆积，形成具有一定强度的板型，管型或弧形制品。压滤成型后的制品经过一定条件的烘干最后经过检验，包装，制成成品。我们真诚地希望与社会各界同仁和朋友、各合作单位和兄弟单位，继续加强合作和交流，让我们携手共进，共同发展。

无石棉微孔硅酸钙是一种白色、硬质的新型保温材料，具有容重轻、强度高、导热系数小、耐高温、耐腐蚀、能切、能锯等特点被广泛应用于电力、冶金、石化、建筑、船舶等领域的设备管道、墙体屋面的保温隔热和防火，隔音。

无石棉硅酸钙板材长度：600mm 宽度：300mm 厚度：30-100mm  
宽、厚度规格任选无石棉硅酸钙管材长度：600mm 直径：25mm-3600mm 厚度：40-100mm  
特殊规格可商议定做

项目	单位	国家标准	公司标准
容重	kg/m <sup>3</sup>	220	220
抗折强度	mpa	0.30	0.30

抗压强度	mpa	0.50	0.50
导热系数	w/m.k	0.062	0.060
使用温度		650	650
线收缩率	%	2.0	2.0

主要特点：1、在容重相近时，本产品无机硬质绝热材料中强度最高。2、在使用温度范围内不变形。3、导热系数比其它硬质块状绝热材料低。4、本产品为无石棉制品，符合环保要求。650 无石棉硅酸钙绝热制品技术性能

项目	单位	公司标准			国家标准
		a型	b型	c型	
容重	kg/m <sup>3</sup>	170	220	500	170 240
抗折强度	mpa	0.25	0.3	1.0	0.2 0.3
抗压强度（变型5%）	mpa	0.5	0.6	2.0	0.4 0.5
线收缩率	%	2	2	2	2 2
导热系数（平均温度70）	w/m.k	0.052	0.056	0.1	0.065 0.065
最高使用温度		650	650	650	650 650
含水率	%	7.5	7.5	7.5	7.5 7.5

我公司是国内研发、设计、生产、制造耐火保温隔音材料及化工产品的现代化企业。我公司产品广泛用于热电、火电、建筑、石油工业、冶炼、船舶、航天、中央空调、冰箱制冷等行业。joyful us corporation is produces the heat preservation building materials, the product of chemical industry and so on multi-domain production factory. altogether occupies a land area of the 62500m<sup>2</sup> investment total assets to surpass 80,000,000 yuan, has the home most advanced equipment and the technology, the introduction large quantities of high-level technical personnel and the managerial talent. our company is the domestic research and development, the design, the production, makes the fireproof heat preservation sound-proof material and the product of chemical industry modernized enterprise. our company product widely is suitable for professions and so on thermoelectricity, thermal power, building, oil industry, smelting, ships, astronautics, central air conditioning, refrigerator refrigeration.

无石棉微孔硅酸钙是一种白色、硬质的新型保温材料，具有容重轻、强度高、导热系数小、耐高温、耐腐蚀、能切、能锯等特点被广泛应用于电力、冶金、石化、建筑、船舶等领域的设备管道、墙体屋面的保温隔热和防火隔音。

the non-asbestos pore calcium silicate is one kind of white, the flinty new thermal insulation material, has the bulk specific gravity to be light, the intensity is high, the thermal conductivity small, thermostable, anti-corrosive, can cut, can saw and so on characteristics widely to apply in domain and so on electric power, metallurgy, petrochemical, building, ships equipment pipelines, the wall roofing heat preservation insulates heat and protects from fire sound-insulated.

### 主要特点

1、在容重相近时，本产品无机硬质绝热材料中强度最高。

2、在使用温度范围内不变形。

3、导热系数比其它硬质块状绝热材料低。

4、本产品为无石棉制品，符合环保要求。

1000 无石棉硅酸钙绝热制品技术性能main feature I, when the bulk specific gravity is close, this product the intensity is highest in the inorganic flinty heat-insulating material. 2, does not distort in the application temperature scope. 3, the thermal conductivity is lower than other flinty massive heat-insulating material. 4, this product for the non-asbestos products, meet the environmental protection requirement. 1000 non-asbestos calcium silicate heat insulation product technical performance

主要用于电力、石化、冶金等工业部门热力设备和管道保温，还可作为各种锅炉耐火砖背衬材料.我们真诚地希望与社会各界同仁和朋友、各合作单位和兄弟单位，继续加强合作和交流，让我们携手共进，共同发展。