

半自动推出式硫化机 液压拖板硫化机

产品名称	半自动推出式硫化机 液压拖板硫化机
公司名称	青岛金港湾机械公司
价格	.00/个
规格参数	类型:平板硫化机 型号:XLB-ZD 样式:立式
公司地址	中国 山东 青岛市 临港工业园188号
联系电话	86 0532 85185085 15806563897

产品详情

类型	平板硫化机	型号	XLB-ZD
样式	立式	运行方式	液压硫化机
品牌	青岛港湾	最大宽度	500 (mm)
切割刀宽	500 (mm)	最大行程	300 (mm)
公称合模力	1. (MN)	电动机功率	4 (KW)
外形尺寸	2000X2000X2500 (m)	重量	3600 (kg)

柱式轨道硫化机 半自动出模硫化机 产地：中国青岛

产品型号：xlb系列

热板规格：400x400 450x450 500x500 550x550 mm按合同

热板间距：200 260 300 350mm按合同

加热方式：电加热

温度范围：0--280 度

柱塞行程：200 260 300 350.....mm

电机功率：4 5.5 kw 或按合同

运行方式：液压

控制方式：电器件组合

机器重量：3000 kg

外形尺寸：2000x2000x1580 mm

工作循环演示（流程演示）：1、放置磨具、开启电源、设置温度、开启预加热

2、设置压制时间、放置产品原料 3、开启工作按钮

4、自动工作循环模式：（1）自动推出磨具（放置原材料）——（2）自动拖入

——（3）压合（合模）——（4）硫化计时——（5）硫化结束——（6）自动开模——（7）自动推出（取出制品）

本产品适用于各种橡胶、硅橡胶、聚氨酯等制品的模压及非模压生产压制，购买时可提前联系咨询，详细了解产品情况，再进行定制适合您产品的机器。

column type rail vulcanizing press semi-automatic the mold vulcanization machine origin: chinese qingdao

the product model: xlb series

the hot plate 400x400 450x450 specifications: 500x500 550x550 mm according to the contract

the hot plate spacing: 200 260 300 350... mm according to the contract

heating mode: electric heating steam heating oil heat transfer (according to the contract)

temperature range: 0-300 degrees

piston stroke: 200 260 300 350... mm

motor power: 2.2 4 5.5 kw or according to the contract

operation mode: hydraulic pressure

control mode: electric parts of combination

machine weight: 16 kg

shape dimension: 2000x2000x1580 mm

the machine is suitable for various rubber products, silica gel products, composite products, handicrafts, bakelite, polyurethane products of moulding and non moulding production, heating mode according to user requirement production.

column type rail vulcanizing press semi-automatic the mold vulcanization machine origin: chinese qingdao

the product model: xlb series

the hot plate 400x400 450x450 specifications: 500x500 550x550 mm according to the contract

the hot plate spacing: 200 260 300 350... mm according to the contract

heating mode: electric heating

temperature range: 0-300 degrees

piston stroke: 200 260 300 350... mm

motor power: 4 5.5 kw or according to the contract

operation mode: hydraulic pressure

control mode: electric parts of combination

machine weight: 3000 kg

shape dimension: 2000x2000x1580 mm

product model xlb - d600x600 1. a force to be called 60mn (mn) 1.60 hot plate specifications (mm) 600x600 hot plate spacing (mm) 350 work up a number of posts "mm () 350 pressure kg m2 unit area () 44.5 dimension (mm) 700x1700x1800 weight (kg) 5100 this machine applies to all kinds of rubber, sulfur plastic models products and the model products.